


**.240 Flanged Spade  
.031 Electro-Tinned Copper  
16-14 AWG (Blue)**

**Spade and Ring Series  
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
0	X			B	✓	✓	4000	50044	
		X		B	✓	✓	3000	50044-8	
			X	B	✓	*	3000	50044-8A	
	X			W	✓	✓	4000	50045	
		X		W	✓	✓	3000	50045-8	
			X	W	✓	*	3000	50045-8A	
2	X			B	✓	✓	4000	50052	
		X		B	✓	✓	3000	50052-8	
			X	B	✓	*	3000	50052-8A	
	X			W	✓	✓	4000	50053	
		X		W	✓	✓	3000	50053-8	
			X	W	✓	*	3000	50053-8A	
4	X			B	✓	✓	4000	50060	
		X		B	✓	✓	3000	50060-8	
			X	B	✓	*	3000	50060-8A	
	X			W	✓	✓	4000	50061	
		X		W	✓	✓	3000	50061-8	
			X	W	✓	*	3000	50061-8A	
6	X			B	✓	✓	4000	50068	
		X		B	✓	✓	3000	50068-8	
			X	B	✓	*	3000	50068-8A	
	X			W	✓	✓	4000	50069	
		X		W	✓	✓	3000	50069-8	
			X	W	✓	*	3000	50069-8A	

Recommended Strip Length  $\frac{3}{32} \pm \frac{1}{32}$   
\* Contact Factory for Latest Agency Approvals.

**S  
P  
A  
D  
E  
&  
R  
I  
N  
G**