



**.300 Notched Spade  
24-18 AWG**


**Spade and Ring Series  
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS	
4	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-4-3		
						Pre Tinned Brass	3C2-4-3		
6	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-6-3		
						Pre Tinned Brass	3C2-6-3		
8	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-8-3		
						Pre Tinned Brass	3C2-8-3		
10	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-10-3		
						Pre Tinned Brass	3C2-10-3		
4	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-3-3		
						Pre Tinned Brass	3C2-3-3		
6	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-5-3		
						Pre Tinned Brass	3C2-5-3		
8	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-7-3		
						Pre Tinned Brass	3C2-7-3		
10	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-9-3		
						Pre Tinned Brass	3C2-9-3		

NOTE: UL & CSA do not recognize 24 AWG terminations

**.300 Notched Spade  
20-14 AWG**

**Spade and Ring Series  
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS	
4	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-4		
						Pre Tinned Brass	3C2-4		
						.032	Brass		3C3-4
							Pre Tinned Brass		3C4-4
6	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-6		
						Pre Tinned Brass	3C2-6		
						.032	Brass		3C3-6
							Pre Tinned Brass		3C4-6
8	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3C1-8		
						Pre Tinned Brass	3C2-8		
						.032	Brass	3C3-8	
							Pre Tinned Brass	3C4-8	