


RECOMMEND P.C.B LAYOUT



■ MATERIAL

HOUSING: NYLON 9T UL94V-0
 CONTACT: PHOSPHOR BRONZE
 PLATING: MATING AREA-SELETED GOLD
 SHELL: TIN/LEAD PLATED:

■ ELECTRICAL

CURRENT RATING: 1 AMP.
 DIELECTRIC WITHSTANDING VOLTAGE: 750 VAC MIN.
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN.
 CONTACT RESISTANCE: 50 MILLIOHMS MAX.

■ ENVIRONMENTAL

TEMPERATURE RANGE: -25°C TO 85°C.

Shell:
 BRASS-Plating TIN

Plating
 01:G/F 30"NICKEL
 15:15"GOLD 50"NICKEL
 30:30"GOLD 50"NICKEL



PART NO. MSB-SW-5AB

DWG NO. MSB-SW-5AB

FILE NO. MUL-N9P01B-X

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X
 .XX
 .XXX
 AWG

DESCRIPTION:

MINI USB (AB TYPE) 5P

AREA

REVISIONS

HK

DATE

煜倫有限公司