

Quad Exclusive OR Gate

The TC74HCT86A is a high speed CMOS EXCLUSIVE OR GATE fabricated with silicon gate C²MOS technology.

It achieves the high speed operation similar to equivalent LSTTL while maintaining the CMOS low power dissipation.




This device may be used as a level converter for interfacing TTL or NMOS to High Speed CMOS. The inputs are compatible with TTL, NMOS and CMOS output voltage levels.

Input and output buffers are provided which offer high noise immunity and stable output.

All inputs are equipped with protection circuits against static discharge or transient excess voltage.


Features

- High Speed: $t_{pd} = 15\text{ns(Typ.)}$ at $V_{CC} = 5\text{V}$
- Low Power Dissipation: $I_{CC} = 1\mu\text{A(Max.)}$ at $T_a = 25^\circ\text{C}$
- Compatible with TTL outputs: $V_{IH} = 2\text{V(Min.)}$
 $V_{IL} = 0.8\text{V(Max.)}$
- Wide Interfacing Ability: LSTTL, NMOS, CMOS
- Output Drive Capability: 10 LSTTL Loads
- Symmetrical Output Impedance: $|I_{OH}| = I_{OL} = 4\text{mA(Min.)}$
- Balanced Propagation Delays: $t_{pLH} = t_{pHL}$
- Pin and Function Compatible with 74LS86



(TOP VIEW)

Pin Assignment



IEC Logic Symbol

Truth Table

A	B	Y
H	H	L
L	H	H
H	L	H
L	L	L

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Supply Voltage Range	V_{CC}	-0.5 - 7	V
DC Input Voltage	V_{IN}	-0.5 - $V_{CC} + 0.5$	V
DC Output Voltage	V_{OUT}	-0.5 - $V_{CC} + 0.5$	V
Input Diode Current	I_{IK}	± 20	mA
Output Diode Current	I_{OK}	± 20	mA
DC Output Current	I_{OUT}	± 25	mA
DC V_{CC} /Ground Current	I_{CC}	± 50	mA
Power Dissipation	P_D	500(DIP)*/180(SOP)	mW
Storage Temperature	T_{stg}	-65 - 150	°C
Lead Temperature 10sec	T_L	300	°C

*500mW in the range of $T_a = -40^\circ\text{C} \sim 65^\circ\text{C}$. From $T_a = 65^\circ\text{C}$ to 85°C a derating factor of -10mW/°C shall be applied until 300mW.

Recommended Operating Conditions

Parameter	Symbol	Value	Unit
Supply Voltage	V_{CC}	4.5 - 5.5	V
Input Voltage	V_{IN}	0 - V_{CC}	V
Output Voltage	V_{OUT}	0 - V_{CC}	V
Operating Temperature	T_{opr}	-40 - 85	°C
Input Rise and Fall Time	t_r, t_f	0 - 500	ns

DC Electrical Characteristics

Parameter	Symbol	Test Condition	$T_a = 25^\circ\text{C}$				$T_a = -40 \sim 85^\circ\text{C}$		Unit	
			V_{CC}	Min	Typ.	Max.	Min.	Max.		
High-Level Input Voltage	V_{IH}	-	4.5 j 5.5	2.0	-	-	2.0	-	V	
Low-Level Input Voltage	V_{IL}	-	4.5 j 5.5	-	-	0.8	-	0.8	V	
High-Level Output Voltage	V_{OH}	$V_{IN} = V_{IH}$ or V_{IL}	$I_{OH} = -20\mu\text{A}$	4.5	4.4	4.5	-	4.4	-	V
			$I_{OH} = -4\text{mA}$	4.5	4.18	4.31	-	4.13	-	
Low-Level Output Voltage	V_{OL}	$V_{IN} = V_{IH}$ or V_{IL}	$I_{OL} = 20\mu\text{A}$	4.5	-	0.0	0.1	-	0.1	V
			$I_{OL} = 4\text{mA}$	4.5	-	0.17	0.26	-	0.33	
Input Leakage Current	I_{IN}	$V_{IN} = V_{CC}$ or GND	5.5	-	-	± 0.1	-	± 1.0	μA	
Quiescent Supply Current	I_{CC}	$V_{IN} = V_{CC}$ or GND	5.5	-	-	1.0	-	10.0		
	ΔI_{CC}	Per Input: $V_{IN} = 0.5\text{V}$ or 2.4V Other Input: V_{CC} or GND	5.5	-	-	2.0	-	2.9	mA	

AC Electrical Characteristics ($C_L = 15\text{pF}$, $V_{CC} = 5\text{V}$, $T_a = 25^\circ\text{C}$, Input $t_r = t_f = 6\text{ns}$)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Output Transition Time	t_{TLH} t_{THL}	–	–	6	12	ns
Propagation Delay Time	t_{PLH} t_{PHL}	–	–	15	23	

AC Electrical Characteristics ($C_L = 50\text{pF}$, Input $t_r = t_f = 6\text{ns}$)

Parameter	Symbol	Test Condition	$T_a = 25^\circ\text{C}$			$T_a = -40 \sim 85^\circ\text{C}$		Unit	
			V_{CC}	Min.	Typ.	Max.	Min.		Max.
Output Transition Time	t_{TLH} t_{THL}	–	4.5 5.5	– –	8 7	15 13	– –	19 16	ns
Propagation Delay Time	t_{PLH} t_{PHL}	–	4.5 5.5	– –	18 16	27 25	– –	34 31	
Input Capacitance	C_{IN}	–	–	–	5	10	–	10	pF
Power Dissipation Capacitance	$C_{PD}(1)$	–	–	–	26	–	–	–	

Note (1) C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.
Average operating current can be obtained by the equation:

$$I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}/4(\text{per Gate})$$

Notes