


48K90US Product Details



48K90US
(1423182-2)

TE Internal Number: 1423182-2



[Search for Replacement Parts](#)

Time Delay Relays

[Not reviewed for RoHS Compliance](#)

Product Highlights:

- 48K International 1/16 DIN Timers Series
- Time Delay Relay
- Input Voltage = 24 - 240 VAC
- Input Voltage = 24 - 240 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Time Delay Relay
- Termination Type = 8-Pin Octal Style Plug

Electrical Characteristics:

- Input Voltage (VAC) = 24 - 240
- Input Voltage (VDC) = 24 - 240
- Contact Rating = 10A Resistive @30 VDC, 120/240 VAC

Body Related Features:

- [Series](#) = 48K International 1/16 DIN Timers

Contact Related Features:

- Mounting Options = Panel Mount, Socket
- Mode of Operation = Interval, On-Delay, On/Interval, Repeat Cycle
- Delay Time = 0.1 seconds to 1 second, 1 minute to 10 minutes, 1 second to 10 seconds, 1 hour to 10 hours, 10 minutes to 100 minutes, 10 seconds to 100 seconds
- Type of Control = Knob
- Repeatability, Max. = ±0.5% ± ±20msec
- Approved Standards = CE Approved, CSA Certified, UL Recognized
- Approx. Dimensions (L x W x H) (mm [in]) = 44.50 x 44.50 x 63.10 [1.753 x 1.753 x 2.486]

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = Not reviewed for ELV/RoHS compliance
- [Lead Free Solder Processes](#) = Not reviewed for lead free solder process

Conditions for Usage:

- Temperature Range (?C) = -25 - +60

Other:

- Brand = Agastat