

1

2

3

4

5

Specifications:

Current Rating:1.5 AC/DC

Voltage Rating:30V AC/DC

Contact Resistance:30m Ohm. Max.

Insulation Resistance:1,000M Ohm. Min.

Withstanding Voltage:500V AC For One Minute

Operating Temperature Range:-40°C ~ +85°C

Materials And Finish:

Insulator:PBT(UL94V-0)

Contact:Copper Alloy

Contact Plating:Gold Plated On Contact and

Tin Plated On Solder Tail Over Nickel Plated

Shell:Copper Alloy With Nickel Plated

How To Order

5075AUR-04-XX

WH:White

BK:Black

No. of Positions

A Type Flank R/A

Recommend P.C.B. Layout

RoHS Compliant

				DRAWN: Cherry Wu	GENERAL TOLERANCE: .X=±0.30 .XX=±0.25 .XXX=±0.15	<b>繼德工業股份有限公司</b> <b>Neltron Industrial Co., Ltd.</b>	DESCRIPTION: USB-A Type Female Flank 90° Dip Type	SIZE <b>A4</b>
E				CHECKED: Dennis Lin				
D				APPROVAL: Mike Wu	UNIT: MM	PART NO: 5075AUR-04-XX		
C					SCALE:			
B				PROJECTION:	SHEET: 1 / 1			
A	23-Oct-2014	(P0164)	Cherry					
REV	DATE	FILE	BY					