


Hutton Close, Crowther Ind Est, Washington, Tyne & Wear NE38 0AH, England  
<mailto:sales@isocom.uk.com> - Tel: +44 (0)191 4166546 - Fax: +44 (0)191 4155055

## Phototransistors


### Single 4 Pin/Dual 8 Pin/Quad 16 Pin

[Optocouplers Catalogue](#)  
[Home Page](#)


### ISFH611A-1 - ISFH611-4, ISFH6116-1 - ISFH6116-4

	Current Transfer Ratio (%) If = 10 mA	Isolation Test Voltage RMS	BVceo	Features
ISFH611A-1	40-80	5300 V	70	TRIOS (TRansparent IO n Shield)
ISFH611A-2	63-125			
ISFH611A-3	100-200			
ISFH611A-4	160-320			
ISFH6116-1	40-80			
ISFH6116-2	63-125			
ISFH6116-3	100-200			
ISFH6116-4	160-320			


**ISFH615A..., ISFH6156..., ISFH617A..., ISFH618A..., ISFH6186...**

	Current Transfer Ratio (%) If = 10 mA	Isolation Test Voltage RMS	BVceo	Features
<a href="#">IS817</a>	50 - 600   If= 5 mA, Vce = 5 V	5000 V		
ISFH615A-1	40-80	5300 V	70	TRIOS (TRansparent IO n Shield)
ISFH615A-2	63-125			
ISFH615A-3	100-200			
ISFH615A-4	160-320			
ISFH615AA	50-600			
ISFH615AAGB	100-600			
ISFH6156-1	40-80			
ISFH6156-2	63-125			
ISFH6156-3	100-200			
ISFH6156-4	160-320			
ISFH617A-1	40-80			
ISFH617A-2	63-125			
ISFH617A-3	100-200			
ISFH617A-4	160-320			
ISFH618A-2	63-125	5300 V	55	Low Current Input. TRIOS (TRansparent IO n Shield)
ISFH618A-3	100-200			
ISFH618A-4	160-320			
ISFH618A-5	250-500			
ISFH6186-2	63-125			
ISFH6186-3	100-200			
ISFH6186-4	160-320			
ISFH6186-5	250-500			


## CH300

	Current Transfer Ratio (%)	Isolation Voltage	BVceo
<a href="#">CH300</a>	50 Min, 120 Typ   If=1mA, Vce= 5V	500 Vdc	30 V


**IS814, ISFH620A..., ISFH6206..., ISFH628A..., ISFH6286...**

	Current Transfer Ratio (%)	Isolation Test Voltage RMS	BV <sub>ceo</sub>	Features
ISFH620A-1	40-125	5300 V	70	TRIOS (Transparent IO on Shield)
ISFH620A-2	63-200			
ISFH620A-3	100-320			
ISFH6206-1	40-125			
ISFH6206-2	63-200			
ISFH6206-3	100-320			
ISFH620AA	50-600	5300 V	70	
ISFH620AGB	100-600			
ISFH628A-2	63-200	5300 V	55	
ISFH628A-3	100-320			
ISFH628A-4	160-500			
ISFH6286-2	63-200			
ISFH6286-3	100-320			
ISFH6286-4	160-500			
<a href="#">IS814</a>	20-300	If=1mA, V <sub>ce</sub> =5V	5000 V	


## IS827

	Current Transfer Ratio (%)	Isolation Test Voltage RMS	BV <sub>ceo</sub>	Features
<a href="#">IS827</a>	50-600	If=5mA, V <sub>ce</sub> =5V	5000 V	


## IS824, ISD620, ISD620GB

	Current Transfer Ratio (%)	Isolation Test Voltage RMS	BV <sub>ceo</sub>	Features
<a href="#">IS824</a>	20-300	If=1mA, V <sub>ce</sub> =5V	5000	
ISD620	50-100	If=10mA	5300 V	70
ISD620GB	100-600			
				Repetitive pinout - emitter and detector

## IS847

	Current Transfer Ratio (%)	Isolation Test Voltage RMS	BV <sub>ceo</sub>	Features
<a href="#">IS847</a>	50-600	If=5mA, V <sub>ce</sub> =5V	5000 V	

## IS844

	Current Transfer Ratio (%) $I_f = 10 \text{ mA}$	Isolation Test Voltage RMS	$BV_{ceo}$	Features	
<a href="#">IS844</a>	20-300	$I_f = 1 \text{ mA}, V_{ce} = 5 \text{ V}$	5000 V		

[Contents](#)