

SUBMINIATURE JACKS & PLUGS 150/3150 SERIES TRS/TTM



Subminiature Jacks & Plugs...

Subminiature concentric twinax/triax connectors increase packing density up to 246%. Designed for high density applications where digital, video pair, or baseband "noise free guarded" circuits are required. The 3-lug, 4-lug, and threaded versions improve mechanical stability and provide "error-free" redundant data bus capability. The wrench crimp version accommodate cables with other jacket diameters up to .215" and the tool crimp versions up to .250".

<p><i>PL155-29 Shown</i></p> <p>CABLE PLUG WRENCH CRIMP</p> <p>3-lug 4-lug Threaded</p> <p>PL155-[△] PL155FL-[△] PL3155-[△]</p>	<p><i>BJ159-29 Shown</i></p> <p>BULKHEAD JACK REAR MOUNT, WRENCH CRIMP</p> <p>3-lug 4-lug Threaded</p> <p>BJ159-[△] BJ159FL-[△] BJ3159-[△]</p> <p>Mounting Hole: D4.125</p>
<p><i>PL155AC-207 Shown</i></p> <p>CABLE PLUG TOOL CRIMP</p> <p>3-lug 4-lug Threaded</p> <p>PL155AC-[△] PL155ACFL-[△] PL3155AC-[△]</p>	<p><i>BJ159AC-207 Shown</i></p> <p>BULKHEAD JACK REAR MOUNT, TOOL CRIMP</p> <p>3-lug 4-lug Threaded</p> <p>BJ159AC-[△] BJ159ACFL-[△] BJ3159AC-[△]</p> <p>Mounting Hole: D4.125</p>
<p><i>PLR3155AC-201 Shown</i></p> <p>RIGHT ANGLE CABLE PLUG TOOL CRIMP</p> <p>3-lug 4-lug Threaded</p> <p>PLR155AC-[△] PLR155ACFL-[△] PLR3155AC-[△]</p>	<p><i>CJ150-29 Shown</i></p> <p>CABLE JACK WRENCH CRIMP</p> <p>3-lug 4-lug Threaded</p> <p>CJ150-[△] CJ150FL-[△] CJ3150-[△]</p>
	<p><i>CJ150AC-207 Shown</i></p> <p>CABLE JACK TOOL CRIMP</p> <p>3-lug 4-lug Threaded</p> <p>CJ150AC-[△] CJ150ACFL-[△] CJ3150AC-[△]</p>

[△]- Refers to Cable Group Table see pages 68-88. "D" mounting holes see page 45.