



TFC Coaxial Connector Information Sheet

Type: QC II– Series 6 Universal, Ni, QuickShield®

F-Type Compression Connector

Series 6: Universal Design
 Nickel (Ni) Plating
 TFC QuickShield® Feature
 (patent US 8,231,412 B2)

Part Numbers:
 TFC-QC2QS-06U-3 (Standard &
 TriShield, &QuadShield)



Features

- Standard 0.300" – 0.250" Cable Preparation using
- Industry Standard Preparation Tools

Connector Characteristics – TFC QC II Compression F-Type

Electrical	Specifications	Limits	Results
Return Loss	ANSI/SCTE 123 2006 Telcordia™ GR-1503 3.5.4	> 30 dB (5-1000 MHz)	Meets or Exceeds
Insertion Loss	Telcordia™ GR-1503 3.5.3	< 0.1 dB (to 350 MHz)	Meets or Exceeds
		< 0.2 dB (to 700 MHz)	Meets or Exceeds
		< 0.3 dB (to 1 GHz)	Meets or Exceeds

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: tfc-qc2qs-06u-3_20140410.doc
 Revision: 4.30.2014
 Page: 1 of 2

Times Fiber Communications, Inc.
 358 Hall Avenue
 Wallingford, CT 06492
 Toll Free +1-800-677-2288
 Phone +1-434-432-1800
 Fax +1-434-432-1821
 www.timesfiber.com
 Sales@timesfiber.com

uncontrolled copy
 All Rights Reserved,
 Specifications subject to change without notice



TFC Coaxial Connector Information Sheet

Type: QC II– Series 6 Universal, Ni, QuickShield®

Connector Characteristics – TFC QC II Compression F-Type

Electrical	Specifications	Limits	Results
Shielding Effectiveness	Telcordia™ GR-1503 3.5.5	> 95 dB (to 300 MHz)	Meets or Exceeds
		> 70 dB (to 1 GHz)	Meets or Exceeds
Screening Attenuation	EN 50289-1-6 / IEC 62153-4-7	> 80 dB (5 MHz - 3.0 GHz)	Reference Information
Dielectric Strength	Telcordia™ GR-1503 3.5.2	> 1.0 kVAC for 1 minute	Meets or Exceeds
Insulation Resistance	Telcordia™ GR-1503 3.5.1	> 5000 Meg-Ω@ 100 VDC	Meets or Exceeds

Mechanical Specifications	Specifications	Limits	Results
Corrosion Resistant	ANSI/SCTE 123 2006	1000 hours	Meets or Exceeds
Cable Application	Telcordia™ GR-1503 3.2.2	< 20 lbf Insertion Force	Meets or Exceeds
Cable Interface	Telcordia™ GR-1503 3.2.3	> 40 lbf Pull Force	Meets or Exceeds
Equipment Interface	Telcordia™ GR-1503 3.2.4	> 10 Matings w/o Damage	Meets or Exceeds
		> 60 in•lbs w/o Damage	Meets or Exceeds
Temperature Cycling with Humidity	Telcordia™ GR-1503 4.1	70°F to 140°F to -40°F Must pass 3.2.3 spec after 7 days	Meets or Exceeds
Loosening Torque	Telcordia™ GR-1503 4.2	> 30 in•lbs after 3 days of 4.1	Meets or Exceeds
Moisture Migration	ANSI/SCTE 64 2004	No Dye Penetration	Meets or Exceeds
Salt Fog	Telcordia™ GR-1503 4.4, 1000 hrs	Return Loss > 30 dB @ 1 GHz	Meets or Exceeds
Environmental Pollutants	Telcordia™ GR-1503 4.5	Return Loss > 30 dB @ 1 GHz	Meets or Exceeds
Vibration	Telcordia™ GR-1503 4.6	Loosening Torque > 32 in•lbs	Meets or Exceeds
Chemical Resistance Outdoor ¹	Telcordia™ GR-1503 4.7	7 Days Exposure	Meets or Exceeds
UV Degradation ¹	Telcordia™ GR-1503 4.8	7 Days Exposure	Meets or Exceeds
Ozone Degradation ¹	Telcordia™ GR-1503 4.10	70 Hour Exposure	Meets or Exceeds

Note ¹: Connectors will not exhibit cracking, swelling, or brittleness.

Customers are reminded that they are SOLELY responsible for confirming that all products are properly installed and used in accordance with all applicable codes and regulations.

Document: tfc-qc2qs-06u-3_20140410.doc
 Revision: 4.30.2014
 Page: 2 of 2

Times Fiber Communications, Inc.
 358 Hall Avenue
 Wallingford, CT 06492
 Toll Free +1-800-677-2288
 Phone +1-434-432-1800
 Fax +1-434-432-1821
 www.timesfiber.com
 Sales@timesfiber.com

uncontrolled copy

All Rights Reserved,
 Specifications subject to change without notice