



MATERIALS:

- INSULATOR: THERMOPLASTIC POLYESTER, UL94V-0
CHEMICAL RESISTANCE, COLOR BLACK
- SHELL: STEEL, NICKEL PLATED
- CONTACT: PHOSPHOR BRONZE, GOLD FLASH
- HEX POST: BRASS, NICKEL PLATED
- WASHER: BRASS OR STEEL, NICKEL PLATED

ELECTRICAL:

- CURRENT RATING: 3 AMPERES
- DIELECTRIC WITHSTANDING VOLTAGE: 1000VAC rms AT SEA LEVEL
- INSULATION RESISTANCE: 5000 MEGOHMS MIN.
- CONTACT RESISTANCE: 10 MILLIOHMS MAX.
- WORKING TEMPERATURE: -55° TO +105° C

**624 SERIES SUBMINIATURE D CONNECTOR
RECEPTACLE(SOCKET) RIGHT ANGLE .200(5.08) FOOTPRINT
WITH THREADED HEX POSTS AND WASHERS**

DRAWN: F.BRIONES DATE: OCT.31/06
CHECKED: DATE:

PART NUMBER
624-009-261-903

EDAC INC
TORONTO, ONTARIO
CANADA
YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF EDAC, INC., AND
SHALL NOT BE REPRODUCED OR COPIED
OR USED AS THE BASIS FOR THE
MANUFACTURE OR SALE OF APPARATUS
WITHOUT WRITTEN PERMISSION.

DRAWING NUMBER
624-009-261-903

ISSUE
1