



Our commitment. Your advantage.

 

- [Products](#)   [Documentation](#)   [Resources](#)   [My Account](#)   [Customer Support](#)

[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > Product Details

## AGR1000 Product Details



**AGR1000**

TE Internal Number: 070669-000



[Contact Product Information Center](#)

### PolySwitch Resettable Devices

[Always ELV Compliant](#) ([Find RoHS Compliant Alternates/Statement of Compliance](#))

**Product Highlights:**

- Automotive, Radial Application
- Family Name = AGR
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = 10 Amps.
- IT (Room Temperature) = 18.50 Amps.

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

- [Add to My Part List](#)   [Request Sample](#)   [Find Similar Products](#)   [Buy Product](#)

### Documentation & Additional Information

**Product Drawings:**

- [AGR1000](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- None Available

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:**

- None Available

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

**Product Type Features:**

- UL Recognized = File No. E74889
- CSA File No. = 78165C

**Electrical Characteristics:**

- [IH \(Room Temperature\) \(Amps.\)](#) = 10
- [IT \(Room Temperature\) \(Amps.\)](#) = 18.50
- [Vmax Operating \(V\)](#) = 16
- [Rmin \(?\)](#) = 0.0034
- [Rmax \(?\)](#) = 0.007
- [R1 Max \[Post Trip\] \(?\)](#) = 0.0102
- Power Dissipation (Typical) (W) = 3.60
- RA Max (?) = 0.0106

**Termination Related Features:**

- Construction = Radial, Through Hole

**Body Related Features:**

- Lead Type = Bottle Kink

**Contact Related Features:**

- [Family Name](#) = AGR

**Configuration Related Features:**

- Coating = Coated

**Industry Standards:**

- [RoHS/ELV Compliance](#) = ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was ELV compliant

**Conditions for Usage:**

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

**Operation/Application:**

- Application = Automotive, Radial

**Packaging Related Features:**

- Packaging Method = Bulk

**Other:**

- Brand = Raychem

[Provide Website Feedback](#) | [Need Help?](#)