

SRMB4/4-FW1-4B

- 2 Connections
- With hinged lever
- With labelling on both sides





Phoenix Mecano Brand

Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	4.0 mm ²	Stripped Length	9.0 mm
Clamping Range min	0.2mm ²	Width	6.0 mm
Clamping Range max	4.0 mm ²	Height	23.0 mm
		Length	38.6 mm
		Length Hole Direct Mounting	31.5 mm

Colours

-  BEIGE, similar RAL 1019
-  BLUE, similar RAL 5015

Connection Diagram



Order Data

Article Designation	Article Number	PU
SRMB4/4-FW1-4B-BEIGE	42345.2	50
SRMB4/4-FW1-4B-BLUE	42345.5	50

Accessoires

Article Designation	Article Number	PU
External Cross-Connector insulated AQI2/6/11	492125.0	50
External Cross-Connector insulated AQI3/6/11	492126.0	50
External Cross-Connector insulated AQI4/6/11	492140.0	10
External Cross-Connector insulated AQI10/6/11	492141.0	10

Ratings

Ratings	UR	CSA	IEC
Rated Voltage	300 V	300 V	400 V
Rated Current	30 A	25 A	32 A
Rated Wire Size	AWG 22-12	AWG 22-12	4.0 mm ²
Rated Impulse Voltage			6 V
Pollution Degree			3