

# REFLECTIVE SWITCHES

Frequency* Range (GHz)	Switch Type	Insertion Loss (dB) max.	Isolation (dB) min.	VSWR max.	Supply Requirements		P/N
					mA +5V dc	mA -5V dc	
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP1T	1.5 1.8 2.8	60	1.70:1 1.80:1 1.90:1	70	50	SW1RD-01
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP1T	1.5 1.8 2.8	60 60 50	1.70:1 1.80:1 1.90:1	70	50	SW1RD-02
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP2T	1.6 2.2 3.0	60	1.80:1 1.90:1 1.90:1	100	70	SW2RD-01
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP2T	1.6 2.2 3.0	60 60 50	1.80:1 1.90:1 1.90:1	100	70	SW2RD-02
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP3T	1.6 2.2 3.2	60	1.80:1 1.90:1 1.90:1	120	70	SW3RD-01
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP3T	1.6 2.2 3.2	60 60 50	1.80:1 1.90:1 1.90:1	120	70	SW3RD-02
0.1 - 4.0 4.0 - 8.0 8.0 - 18.0	SP4T	1.8 2.2 3.3	60 60 50	2.00:1	150	80	SW4RD-01
0.01 - 2.5	SP1T	0.50			70	50	SW1L-01
0.01 - 2.5	SP2T	1.00	60	2.00:1	100	70	SW2L-01
0.01 - 2.5	SP3T	1.50			120	70	SW3L-01

\* Other frequency bands available, consult factory.  
See outlines on page 76.

Miscellaneous  
Components

48 Industrial West • Clifton, NJ 07012 • Tel: (973) 779-6262 • Fax: (973) 779-2727  
Web Site: [www.pulsarmicrowave.com](http://www.pulsarmicrowave.com) • E-Mail: [sales@pulsarmicrowave.com](mailto:sales@pulsarmicrowave.com)