

**Screw Clamp 32/35 mm DIN-Rail Terminals
Circuit Protection
Single Level Fuse**

For Circuit Breakers, see pages 2/20-26

SAKS 1

SAKS 1 Neon lamp

SAKS 1/LED

**SAKS 3
SAKS 3/35**



Dimensions

Width/Length/Height mm (in.)

With TS 35x7.5

With TS 32

Insulation stripping length

mm (in.)

Technical data

Rated voltage/rated current/wire size

UL

CSA

VDE

Nm (lb. in.)

M

Ordering data

Version

Beige Wemid

Krg

Krg

24VDC

24VAC

24VAC/DC

48VDC

48VAC

48VAC/DC

40-50VDC

40-50VAC

100 VDC

100VAC/DC

110VAC

220VDC

220VAC

220VAC/DC

End plate/Partition



G fuse cartridges, 5 x 20mm

Rated current (A):

Rated voltage: 250VAC

Switching capacity: 1500A

(at 250V, 50 Hz, cos = 0.7)

Screw cap/disconnect lever (spare)

Screw Cap

Black screw cap

Marking tags

Note: Part numbers are shown for a single card of pre-printed tags numbered 1-50. For additional information, see section 5.

Consecutive horizontal

Consecutive vertical

See Section 5 for mounting rails, end brackets, test taps, additional marking material and accessories

* Voltage limit dependent on the version selected.

** For 1 1/4" x 1/4" fuse

*** For 5 x 30 mm fuse

5 x 20 mm fuse

5 x 20 mm fuse

5 x 20 mm fuse

1 1/4" x 1/4" fuse

13 / 54 / 54 (.51"/2.13"/2.13")

13 / 54 / 61 (.51"/2.13"/2.4")

12 (.47")

600V / 6A / #22...10 AWG

600V / 10A / #26...10 AWG

500V / 10A / 10mm²

1.2 (26)

4

13 / 54 / 54 (.51"/2.13"/2.13")

13 / 54 / 61 (.51"/2.13"/2.4")

12 (.47")

V* / 6A / #22...10 AWG

* / 10A / #26...10 AWG

220V/110V / 10A / 10mm²

1.2 (26)

4

13 / 54 / 54 (.51"/2.13"/2.13")

13 / 54 / 61 (.51"/2.13"/2.4")

12 (.47")

V* / 6A / #22...10 AWG

* / 10A / #26...10 AWG

24V / 10A / 10mm²

1.2 (26)

4

13 / 54 / 55 (.51"/2.13"/2.17")

13 / 54 / 61 (.51"/2.13"/2.4")

12 (.47")

600V / 10A / #22...10 AWG

600V / 10A / #22...10 AWG

500V / 10A / 10mm²

1.2 (26)

4

50160

50162

(thickness mm)

Krg

HP

AP (2.5)

For

TW (2.0)

0.10 rapid-blow

0.20 rapid-blow

0.25 rapid-blow

0.50 rapid-blow

1.0 rapid-blow

1.6 rapid-blow

2.0 rapid-blow

2.5 rapid-blow

3.15 rapid-blow

4.0 rapid-blow

5.0 rapid-blow

6.3 rapid-blow

Brass slug

Screw Cap

Black screw cap

Print

Consecutive horizontal

Consecutive vertical

FW 5

FS 5

30612

AP (2.5)

For

TW (2.0)

0.10 rapid-blow

0.20 rapid-blow

0.25 rapid-blow

0.50 rapid-blow

1.0 rapid-blow

1.6 rapid-blow

2.0 rapid-blow

2.5 rapid-blow

3.15 rapid-blow

4.0 rapid-blow

5.0 rapid-blow

6.3 rapid-blow

Brass slug

Screw Cap

Black screw cap

Print

Consecutive horizontal

Consecutive vertical

FW 5

FS 5

19992

AP (2.5)

For

TW (2.0)

0.10 rapid-blow

0.20 rapid-blow

0.25 rapid-blow

0.50 rapid-blow

1.0 rapid-blow

1.6 rapid-blow

2.0 rapid-blow

2.5 rapid-blow

3.15 rapid-blow

4.0 rapid-blow

5.0 rapid-blow

6.3 rapid-blow

Brass slug

Screw Cap

Black screw cap

Print

Consecutive horizontal

Consecutive vertical

FW 5

FS 5

37142

AP (2.5)

For

TW (2.0)

0.10 rapid-blow

0.20 rapid-blow

0.25 rapid-blow

0.50 rapid-blow

1.0 rapid-blow

1.6 rapid-blow

2.0 rapid-blow

2.5 rapid-blow

3.15 rapid-blow

4.0 rapid-blow

5.0 rapid-blow

6.3 rapid-blow

Brass slug

Screw Cap

Black screw cap

Print

Consecutive horizontal

Consecutive vertical

FW 5

FS 5

22582

AP (2.5)

For

TW (2.0)

0.10 rapid-blow

0.20 rapid-blow

0.25 rapid-blow

0.50 rapid-blow

1.0 rapid-blow

1.6 rapid-blow

2.0 rapid-blow

2.5 rapid-blow

3.15 rapid-blow

4.0 rapid-blow

5.0 rapid-blow

6.3 rapid-blow

Brass slug

Screw Cap

Black screw cap

Print

Consecutive horizontal

Consecutive vertical

FW 5

FS 5

24892**

AP (2.5)

For

TW (2.0)

0.10 rapid-blow

0.20 rapid-blow

0.25 rapid-blow

0.50 rapid-blow

1.0 rapid-blow

1.6 rapid-blow

2.0 rapid-blow

2.5 rapid-blow

3.15 rapid-blow

4.0 rapid-blow

5.0 rapid-blow

6.3 rapid-blow

Brass slug

Screw Cap

Black screw cap

Print

Consecutive horizontal