

## General Information

Extended Product Type:	S201MT-K3NA
Product ID:	2CDS271106R0317
EAN:	4016779767125
Catalog Description:	Miniature Circuit Breaker - S200MT - 2P - K
Long Description:	S200MT miniature circuit breakers are designed especially for traction and railway applications. Acc. NF F 16-101/102 the product range S200MT is classified with Exigence 3, enabling the use in all parts of the vehicle. They are current limiting and have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 10 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200MT comply with IEC/EN 60898-1 and IEC/EN 609 47-2. All system pro M compact accessories can be used. Including the bottom-fitting auxiliary contact S2C-Hxx providing the possibility of 50% space saving and the creation of group signals.

## Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Miniature Circuit Breakers MCBs

## Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362010

## Popular Downloads

Data Sheet, Technical Information:	2CDC002053D0204
Instructions and Manuals:	2CDC002053D0204

## Dimensions

Product Net Width:	35 mm
Product Net Depth:	69 mm
Product Net Height:	88 mm
Product Net Weight:	0.25 kg

## Technical

Standards:	IEC/EN 60947-2
Number of Poles:	2
Tripping Characteristic:	K
Rated Current ( $I_n$ ):	3 A
Rated Operational Voltage:	acc. to IEC 60947-2 230 V AC
Power Loss:	3.8 W at Rated Operating Conditions per Pole 1.9 W
Rated Insulation Voltage ( $U_i$ ):	acc. to IEC/EN 60664-1 440 V
Operational Voltage:	Maximum (Incl. Tolerance) 253 V AC Minimum 12 V AC
Rated Frequency (f):	50 Hz 60 Hz
Rated Short-Circuit Capacity ( $I_{cn}$ ):	10 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(230 V AC) 15 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(230 V AC) 11.3 kA
Energy Limiting Class:	3
Overvoltage Category:	III
Pollution Degree:	3
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	4 kV (6.2 kV @ sea level) kV (5.0 kV @ 2000 m) kV
Dielectric Test Voltage:	50 / 60 Hz, 1 min: 2 kV
Housing Material:	Insulation Group I, RAL 7035
Actuator Type:	Insulation group II, black, sealable
Contact Position Indication:	ON / OFF
Degree of Protection:	IP20
Remarks:	IP40 in enclosure with cover
Electrical Endurance:	20000 AC cycle

	10000 AC cycle
<b>Mechanical Endurance:</b>	20000 cycle
<b>Terminal Type:</b>	Screw Terminals
<b>Screw Terminal Type:</b>	Failsafe Bi-directional Cylinder-lift Terminal
<b>Connecting Capacity:</b>	Busbar 10 / 10 mm&#178; Flexible with Ferrule 0.75 ... 16 mm&#178; Flexible 0.75 ... 16 mm&#178; Rigid 0.75 ... 25 mm&#178; Stranded 0.75 ... 25 mm&#178;
<b>Tightening Torque:</b>	2.8 N&#183;m
<b>Recommended Screw Driver:</b>	Pozidriv 2
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Mounting Position:</b>	Any

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 &#176;C Storage -40 ... +70 &#176;C
<b>Resistance to Shock acc. to IEC 60068-2-27:</b>	30g / 3 shocks / 11 ms
<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
<b>Environmental Conditions:</b>	28 cycles with 55 &#176;C / 90-96 % and 25 &#176;C / 95-100 %

## Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	2CDK400594D2702
--	-----------------

## Container Information

<b>Package Level 1 Units:</b>	5 piece
<b>Package Level 1 Width:</b>	92 mm
<b>Package Level 1 Length:</b>	183 mm
<b>Package Level 1 Height:</b>	80 mm
<b>Package Level 1 Gross Weight:</b>	1.3 kg
<b>Package Level 1 EAN:</b>	4016779827539

## Classifications

<b>Object Classification Code:</b>	F
<b>ETIM 4:</b>	EC000042 - Miniature circuit breaker (MCB)
<b>ETIM 5:</b>	EC000042 - Miniature circuit breaker (MCB)
<b>ETIM 6:</b>	EC000042 - Miniature circuit breaker (MCB)
<b>eClass:</b>	7.0 27141901
<b>UNSPSC:</b>	39121614

## Accessories [Show accessory images](#)

32 Products		Filter	<input type="text"/>
Identifier	Description	Type	Qty Unit Of Measure
<a href="#">2CCA880100R0001</a>	Strom-Messsystem Sensor CMS-100PS 80A, 18mm für pro M compact u. SMISSLINE	CMS-100PS	1 piece
<a href="#">2CCA880101R0001</a>	Strom-Messsystem Sensor CMS-101PS 40A, 18mm für pro M compact u. SMISSLINE	CMS-101PS	1 piece
<a href="#">2CCA880102R0001</a>	Strom-Messsystem Sensor CMS-102PS 20A, 18mm für pro M compact u. SMISSLINE	CMS-102PS	1 piece
<a href="#">2CDS200909R0001</a>	S2C-A1 - Arbeitsstromauslöser	S2C-A1	1 piece
<a href="#">2CDS200909R0002</a>	S2C-A2 - Arbeitsstromauslöser	S2C-A2	1 piece
<a href="#">2CDS200912R0001</a>	S2C-H6R - Hilfskontakt	S2C-H6R	1 piece
<a href="#">2CDS200918R0001</a>	S2C-NT - Manueller Neutralleiter	S2C-NT	1 piece
<a href="#">2CDS200922R0001</a>	S2C-S/H6R - Signalkontakt / Hilfsschalter	S2C-S/H6R	1 piece
<a href="#">2CDS200936R0001</a>	S2C-H11L - Hilfskontakt	S2C-H11L	1 piece
<a href="#">2CDS200936R0002</a>	S2C-H20L - Hilfskontakt	S2C-H20L	1 piece
<a href="#">2CDS200936R0003</a>	S2C-H02L - Hilfskontakt	S2C-H02L	1 piece
<a href="#">2CDS200946R0001</a>	S2C-H6-11R - Hilfsschalter	S2C-H6-11R	1 piece
<a href="#">2CDS200946R0002</a>	S2C-H6-20R - Hilfskontakt	S2C-H6-20R	1 piece
<a href="#">2CDS200946R0003</a>	S2C-H6-02R - Hilfskontakt	S2C-H6-02R	1 piece
<a href="#">2CDS200970R0001</a>	S2C-H01 - Hilfskontakt	S2C-H01	1 piece

Identifier	Description	Type	Qty	Unit Of Measure
2CSS200911R0001	S2C-UA 12 DC - Unterspannungsauslöser	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC - Unterspannungsauslöser	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC - Unterspannungsauslöser	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC - Unterspannungsauslöser	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC - Unterspannungsauslöser	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC - Unterspannungsauslöser	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC - Unterspannungsauslöser	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC - Unterspannungsauslöser	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC - Unterspannungsauslöser	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC - Unterspannungsauslöser	S2C-UA 230 DC	1	piece
2CSS200998R0001	S2C-BP - Mechanischer Auslöser	S2C-BP	1	piece
2CSS200999R0001	S2C-EST - Stecksockel	S2C-EST	1	piece
2CSS201997R0013	S2C-CM1 - Motorantrieb	S2C-CM1	1	piece
2CSS203997R0013	S2C-CM2/3 - Motorantrieb	S2C-CM2/3	1	piece
2CSS204997R0013	S2C-CM4 - Motorantrieb	S2C-CM4	1	piece
GHS2001901R0003	S2C-DH - Antrieb	S2C-DH	1	piece

