



#### General ordering data

Order No.	1812540200
Part designation	SAIL-M12BG-4S2.0Q
EAN	4032248711482
Qty.	1 pc(s).

#### Technical data

Ambient temperature, max.	85 °C
Ambient temperature, min.	-25 °C
Cable diameter, max.	5.4 mm
Cable diameter, min.	5 mm
Connection cross-section	0.25 (5-pole) / 0.34 (3- and 4-pole)
Contact material	Ni/Au
Contact surface	gold-plated
Contact tube diameter	M12
Core cross-section	0.34 mm <sup>2</sup>
Material	PUR/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	250 V DC / 300 V AC
Sheathing colour	black
No. of poles	4
Version	Female socket, straight

#### Similar products

Order No.	Part designation	Version
1812541000	SAIL-M12BG-4S10Q	Sensor/Actuator line, One end without connector, LED: No, 10.00 m, PUR/PVC
1812541500	SAIL-M12BG-4S15Q	Sensor/Actuator line, One end without connector, LED: No, 15.00 m, PUR/PVC
1812540500	SAIL-M12BG-4S5.0Q	Sensor/Actuator line, One end without connector, LED: No, 5.00 m, PUR/PVC

1808960000	SAIL-M12BG-4S8.0Q	
1812540150	SAIL-M12BG-4S1.5Q	Sensor/Actuator line, One end without connector, LED: No, 1.50 m, PUR/PVC
1812541700	SAIL-M12BG-4S17Q	
1812542000	SAIL-M12BG-4S20Q	
1812540300	SAIL-M12BG-4S3.0Q	Sensor/Actuator line, One end without connector, LED: No, 3.00 m, PUR/PVC
1812543000	SAIL-M12BG-4S30Q	Sensor/Actuator line, One end without connector, LED: No, 30.00 m, PUR/PVC
1812543500	SAIL-M12BG-4S35Q	Sensor/Actuator line, One end without connector, LED: No, 35.00 m, PUR/PVC