



Specifications:  
 Insulator: L.C.P  
 Contact: Phosphor Bronze, t=0.2mm  
 Shell: Phosphor Bronze, t=0.30mm  
 Current rating: 1 A Max.  
 Dielectric withstanding voltage:  
 750V(ac) for 1 min.  
 Contact resistance: 30 Milliohms Max.  
 Insulation resistance: 1000 Megohms Min.  
 Total mating force: 3.5 Kgf Max.  
 Total unmating force: 1.0 Kgf Min.  
 Temperature range: -55°C to +85°C

4	shell 2			Nickel plated all
3	shell 1			Tin plated all
				Selctive 3u" Au plated on mating area
2	Contact	8		
1	Housing	1		Black
No.	Name	Q'ty	Part No.	Finish

**AUK** A NUMBER OF AUK GROUP  
 太聯事業股份有限公司  
 AUK CONTRACTORS CO., LTD.

DRAWING No.  
 MSB08SW

APPROVED BY MEI  
 CHECKED BY BECKY  
 DRAWING BY HZF

UNLESS OTHERWISE SPECIFIED  
 TOLERANCES ARE  
 .X ±0.38  
 .XX ±0.25  
 ANG.

SCALE NONE

REV. A0

UNIT mm

NO. REV. A0

NEW RELEASE REVISIONS

MEI CHK DATE