



SPECIFICATIONS
 Current Rating: 7A AC/DC
 Insulation Resistance: 1000M Ω
 Contact Resistance: 20m Ω max
 Contact Material: Brass
 Insulation Material: See Options
 Withstanding: 1500V AC
 Temperature Range: -25C to +105C

Dimensions		
Poles	A	B
2	3.96	7.86
3	7.92	11.82
4	11.88	15.78
5	15.84	19.74
6	19.80	23.70
7	23.76	27.66
8	27.72	31.62
9	31.68	35.58
10	35.64	39.54
11	39.60	43.50
12	43.56	47.46
13	47.52	51.42
14	51.48	55.38
15	55.44	59.34

Series	Type	Positions	Material	Color	Plating
JS-CH	1120X	XX	X	XX	XX
Pluggable Connector	Vertical Wafer X: Blank=Standard H=Holding Type	02-15	Blank=Nylon 66 GF=Nylon 66 + Glass Fill	Blank=Natural (std) BK=Black BL=Blue	Blank=Tin GD=Gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/11
				Checked	Lizzy	05/15/11
				Drawn	Tina	05/15/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1120X-XX-X-XX-XX**

Description: 3.96mm Wire to Board Connector

