





2.0" 5 × 7 DOT MATRIX DISPLAYS

YELLOW GMA 2875C GMC 2875C
HER GMA 2975C GMC 2975C
GREEN GMA 2475C GMC 2475C
BICOLOR RED/GREEN GMA 2675C



PACKAGE DIMENSIONS

A. GMX2X75C



ST2639

B. GMA2675C



ST2640

DESCRIPTION

These are 5 × 7 dot matrix displays with large emitting area (0.2" diameter) LED sources. The GMX2X75C series are single color displays with the exception of GMA2675C which is a bicolor of red/green displays.

All displays have gray face and white dot color. Other face or dot colors are available with minimum requirement.

The X in GMX denotes row anode or row cathode.

FEATURES

- 2.0" (50.7 mm) character height
- Low power requirement
- High contrast & brightness
- Wide viewing angle 130°
- 5 × 7 array with X-Y select
- Compatible with USASCII and EBCDIC codes
- X-Y stackable
- Choice of two matrix orientation anode or cathode column
- Easy mounting on PCB
- Categorized for luminous intensity
- Single color displays have the choice of 3 bright colors — yellow/orange/green
- Multicolor color displays are applicable to 3 bright colors — greens, orange (HER) and yellow (green and HER mixed)

NOTES:

1. ALL PINS ARE 00.5 (.02).
2. DIMENSIONS IN MILLIMETERS (INCH), TOLERANCE IS ±0.25 (.01) UNLESS OTHERWISE NOTED.




**2.0" 5 × 7
DOT MATRIX DISPLAYS**

ABSOLUTE MAXIMUM RATING ($T_A = 25^\circ\text{C}$ unless otherwise specified)				
PARAMETER	YELLOW	HER	GREEN	UNITS
Power dissipation per dot/color	60	70	75	mW
Peak forward current per dot/color (duty cycle 1/10, 10KHz)	80	100	100	mA
Continuous I_f per dot/color	20	25	25	mA
Reverse voltage V_R per dot/color	5	5	5	V
Operating and storage temperature range	-25°C to +85°C			
Soldering time at 260°C (1/16 inch below seating plane)	3 sec			

MODEL NUMBERS						
PART NO.			MULTI-COLOR	DESCRIPTION	PACKAGE DIMENSION	INTERNAL CIRCUIT DIAGRAM
YELLOW	HER	GREEN				
GMC2875C	GMC2975C	GMC2475C		Anode column, cathode row	A	A
GMA2875C	GMA2975C	GMA2475C		Cathode column, anode row	A	B
			GMA2675C	Cathode column, anode row	B	C

ELECTRICAL/OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise specified) GMX 2875C					
PARAMETER	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
Average luminous intensity		3000		μcd	$I_F = 20 \text{ mA}$
Peak emission wavelength		585		nm	$I_F = 20 \text{ mA}$
Spectral line half-width		30		nm	$I_F = 20 \text{ mA}$
Forward voltage, any dot		2.1	2.8	V	$I_F = 20 \text{ mA}$
Reverse voltage, any dot			100	μA	$V_R = 5 \text{ V}$



ELECTRICAL/OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise specified)					
GMX 2975C					
PARAMETER	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
Average luminous intensity		3000		μcd	$I_F = 20\text{ mA}$
Peak emission wavelength		635		nm	$I_F = 20\text{ mA}$
Spectral line half-width		30		nm	$I_F = 20\text{ mA}$
Forward voltage, any dot		2.1	2.8	V	$I_F = 20\text{ mA}$
Reverse voltage, any dot			100	μA	$V_R = 5\text{ V}$

TYPICAL ELECTRICAL/OPTICAL CHARACTERISTIC CURVES
($T_A = 25^\circ\text{C}$ Unless otherwise specified)

C3031

C3032

C3033

C3034


C3036

C3035

Fig. 1. Forward Current vs. Forward Voltage Fig. 2. Spectral Response Fig. 3. Relative Luminous Intensity vs. Forward Current

Fig. 4. Maximum Allowable DC Current Per Segment vs. A Function of Ambient Temperature Fig. 5. Luminous Intensity vs. Duty Cycle Fig. 6. Max. Peak Current vs. Duty Cycle % (Refresh Rate $f = 1\text{ KHz}$)

ELECTRICAL/OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise specified)					
GMX 2475C					
PARAMETER	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
Average luminous intensity		3000		μcd	$I_f = 20 \text{ mA}$
Peak emission wavelength		565		nm	$I_f = 20 \text{ mA}$
Spectral line half-width		30		nm	$I_f = 20 \text{ mA}$
Forward voltage, any dot		2.1	2.8	V	$I_f = 20 \text{ mA}$
Reverse voltage, any dot			100	μA	$V_R = 5 \text{ V}$






**2.0" 5 × 7
DOT MATRIX DISPLAYS**


PIN CONNECTION			
PIN NO.	GMC2X75C	GMA2X75C	GMA2675C
1	Cathode row 5	Anode row 5	Cathode column 1 green
2	Cathode row 7	Anode row 7	Cathode column 2 green
3	Anode column 2	Cathode column 2	Cathode column 2 HER
4	Anode column 3	Cathode column 3	Cathode column 3 HER
5	Cathode row 4	Anode row 4	Anode row 6
6	Anode column 5	Cathode column 5	Anode row 7
7	Cathode row 6	Anode row 6	Cathode column 4 HER
8	Cathode row 3	Anode row 3	Anode row 5
9	Cathode row 1	Anode row 1	No connection
10	Anode column 4	Cathode column 4	Cathode column 5 green
11	Anode column 3	Cathode column 3	Cathode column 5 HER
12	Cathode row 4	Anode row 4	Cathode column 4 green
13	Anode column 1	Cathode column 1	Anode column 3 green
14	Cathode row 2	Anode row 2	Anode row 4
15			Anode row 2
16			Anode row 1
17			Anode row 3
18			Cathode column 1 HER

INTERNAL CIRCUIT DIAGRAM

A. GMC2X75C



B. GMA2X75C



C. GMA2675C

