



U74HC02

CMOS IC


HCQUADRUPLE 2-INPUT NOR GATES

DESCRIPTION

The **U74HC02** contains four independent 2-input NOR gates, which provides the Function $Y=A+B$ in positive logic.

FEATURES

- * Operation voltage range: 2~6V
- * Low power dissipation: $I_{CC}=2\mu A(\text{Max})$
- * High speed: $t_{pd}=8\text{ns}(\text{Typ}) V_{CC}=6\text{V}$
- * Low input current: 100nA Max




Lead-free: U74HC02L
 Halogen-free: U74HC02G

ORDERING INFORMATION

Ordering Number			Package	Packing
Normal	Lead Free Plating	Halogen Free		
U74HC02-S14-T	U74HC02L-S14-T	U74HC02G-S14-T	SOP-14	Tube
U74HC02-S14-R	U74HC02L-S14-R	U74HC02G-S14-R	SOP-14	Tape Reel
U74HC02-P14-T	U74HC02L-P14-T	U74HC02G-P14-T	TSSOP-14	Tube
U74HC02-P14-R	U74HC02L-P14-R	U74HC02G-P14-R	TSSOP-14	Tape Reel

<p>U74HC02L-S14-T</p> <p>(1)Packing Type (2)Package Type (3)Lead Plating</p>	<p>(1) R: Tape Reel, T: Tube (2) S14: SOP-14, P14: TSSOP-14 (3) G: Halogen Free, L: Lead Free, Blank: Pb/Sn</p>
--	--

■ PIN CONFIGURATION



■ FUNCTION TABLE

INPUT(A)	INPUT(B)	OUTPUT(Y)
L	L	H
L	H	L
H	L	L
H	H	L

■ LOGIC DIAGRAM



■ ABSOLUTE MAXIMUM RATING (unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V_{CC}	-0.5~7	V
Input Clamp Current	I_{IK}	±20	mA
Output Clamp Current	I_{OK}	±20	mA
Output Current	I_{OUT}	±25	mA
V_{CC} or GND Current	I_{CC}	±50	mA
Storage Temperature	T_{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
 Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ RECOMMENDED OPERATING CONDITIONS

	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V_{CC}		2	5	6	V
Input Voltage	V_{IN}		0		V_{CC}	V
Output Voltage	V_{OUT}		0		V_{CC}	V
Input Transition Rise or Fall Rate	t_R, t_F	$V_{CC}=2V$			1000	ns
		$V_{CC}=4.5V$			500	
		$V_{CC}=6V$			400	
Operating Temperature	T_A		-40		85	°C

■ STATIC CHARACTERISTICS ($T_a = 25^\circ C$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT	
High-Level Input Voltage	V_{IH}	$V_{CC}=2V$	1.5			V	
		$V_{CC}=4.5V$	3.15				
		$V_{CC}=6V$	4.2				
Low-Level Input Voltage	V_{IL}	$V_{CC}=2V$			0.5	V	
		$V_{CC}=4.5V$			1.35		
		$V_{CC}=6V$			1.8		
High-Level Output Voltage	V_{OH}	$V_{CC}=2V, I_{OH} 20\mu A$	$V_{IN} = V_{IH} \text{ or } V_{IL}$	1.9	1.998	V	
		$V_{CC}=4.5V, I_{OH}=20\mu A$		4.4	4.999		
		$V_{CC}=6V, I_{OH}=20\mu A$		5.9	5.999		
		$V_{CC}=4.5V, I_{OH}=4mA$		3.98	4.3		
		$V_{CC}=6V, I_{OH}=5.2mA$		5.48	5.8		
Low-Level Output Voltage	V_{OL}	$V_{CC}=2V, I_{OL}=20\mu A$	$V_{IN} = V_{IH} \text{ or } V_{IL}$		0.002	0.1	V
		$V_{CC}=4.5V, I_{OL}=20\mu A$			0.001	0.1	
		$V_{CC}=6V, I_{OL}=20\mu A$			0.001	0.1	
		$V_{CC}=4.5V, I_{OL}=4mA$			0.17	0.26	
		$V_{CC}=6V, I_{OL}=5.2mA$			0.15	0.26	
Input Leakage Current	$I_{I(LEAK)}$	$V_{CC}=6V, V_{IN}=V_{CC}$ or GND		±0.1	±100	nA	
Quiescent Supply Current	I_Q	$V_{CC}=6V, V_{IN}=V_{CC}$ or GND, $I_{OUT}=0$			2	μA	
Input Capacitance	C_{IN}	$V_{CC}=2V\sim 6V$		3	10	pF	


■ DYNAMIC CHARACTERISTICS ($T_a=25^\circ\text{C}$, Input: $t_R=t_F=6\text{ns}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay from Input(A or B) to Output(Y)	t_{PLH}, t_{PHL}	$V_{CC}=2\text{V}, C_L=50\text{pF}$		45	90	ns
		$V_{CC}=4.5\text{V}, C_L=50\text{pF}$		9	18	
		$V_{CC}=6\text{V}, C_L=50\text{pF}$		8	15	
Output Transition Time	t_t	$V_{CC}=2\text{V}$		38	75	ns
		$V_{CC}=4.5\text{V}$		8	15	
		$V_{CC}=6\text{V}$		6	13	


■ OPERATING CHARACTERISTICS ($T_a=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	Cpd	No load		22		pF

■ TEST CIRCUIT AND WAVEFORMS



Note : C_L includes probe and jig capacitance.



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.