



107829-5 Product Details

[Share](#) | [Print](#) | [Email](#)


107829-5

Fiber Optic Attenuators

Not reviewed for RoHS Compliance

Product Highlights:

- Attenuator - Fiber Optic
- Fiber Optic Attenuator Type = Bandpass
- Attenuation = 5.0 dB
- Attenuator Style = Build Out
- Operating Wavelength = 1260 - 1360 nm, 1430 - 1580 nm

[View all Features](#)

TE Internal Number: 107829-5

Superseded

[Search for Replacement Parts](#)

[Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Related Products:</p> <ul style="list-style-type: none"> • Tooling
---	---

Feedback

Product Features (Please use the Product Drawing for all design activity)

<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Type = Attenuator - Fiber Optic • Fiber Optic Attenuator Type = Bandpass • Type of Connector = SC • Sealed = No <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Attenuation (dB) = 5.0 • Operating Wavelength (nm) = 1260 - 1360, 1430 - 1580 • Attenuation Value = Fixed <p>Body Features:</p> <ul style="list-style-type: none"> • Attenuator Style = Build Out • Reflectance (less than or equal) (dB) = -45 	<p>Configuration Features:</p> <ul style="list-style-type: none"> • Mode = Singlemode <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not reviewed for ELV/RoHS compliance • Lead Free Solder Processes = Not reviewed for lead free solder process <p>Packaging Features:</p> <ul style="list-style-type: none"> • Fiber Packaging Style = None <p>Other:</p> <ul style="list-style-type: none"> • Brand = AMP • Comment = Designed to comply with Telcordia GR-910
--	--

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



