

## **CRIMP RINGS & SPADES**





✓ Active



## TERMINAL, PIDG R SLTD 12-10 1/4

PIDG | PIDG

321611

TE Internal Number: 321611

Always EU RoHS/ELV Compliant

Terminal Shape Ring Tongue

Stud Diameter 6.35 mm [ .25 in ]

Tongue Thickness 1.07 mm [.042 in]

Sealed No

Heavy Duty No

**Product Drawings** 

**Body Features** 

Wire Terminal Pidg Slotted Ring Tongue Wire Size 12-10 PDF (TIFF AVAILABLE) English

Wire Terminal Pidg Slotted Ring Tongue Wire Size 12-10 PDF (TIFF AVAILABLE) English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	No
	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Stud Size	M6
	Shape Code	Slotted Ring-001
	Terminal Features	Slotted
	Barrel Style	Standard
Electrical Characteristics	Voltage (Max) (V)	300

Copper, Tin

Plating Material

	Insulation Type	Pre-Insulated
Contact Features	Terminal Shape  Terminal Orientation	Ring Tongue Straight
Dimensions	Stud Diameter	6.35 mm [ .25 in ]
	Tongue Thickness	1.07 mm [ .042 in ]
	Wire Insulation Diameter (Max)	7.62 mm [ .3 in ]
	Wire Insulation Diameter (in)	.173
	Wire Size (AWG)	12 – 10
	Wire Size (mm²)	3 – 6
	Wire Size (CMA)	5180 – 13100
	Overall Length (in)	1.39
	Barrel Inside Diameter (Min) (in)	.315
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Carton
	Packaging Quantity	1000
Other	Barrel Color	Yellow
	Comment	Insulation - Vinyl

Statement of Compliance PDF

VIEW ALL PRODUCT COMPLIANCE

**Product Compliance** 

Insulation Material

Vinyl