

ADS-A3A8	SMA Plug To SMA Jack 18GHz VSWR 1.2		50Ω
Parts	Material	Plating (Micro-inch)	
Renber Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Gasket	Silicone		
Contact Pin	Beryllium Copper	Gold 4 over nickel phosphorous alloy 80 over copper 20	
Insulator	Teflon		
Body	Stainless	Passivated	
Coupling Nut	Stainless	Passivated	
Weight: 3.24 g			

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

ADS-A3A8	SMA Plug To SMA Jack 18GHz VSWR 1.2																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 342 531 394" style="border: 1px solid black;">Interface</td> </tr> <tr> <td data-bbox="129 400 774 436">Standard</td> <td data-bbox="774 400 1481 436">MIL-STD-348B</td> </tr> <tr> <td data-bbox="129 448 774 483">Mechanically compatible with</td> <td data-bbox="774 448 1481 483">2.92 & 3.5</td> </tr> </table>		Interface		Standard	MIL-STD-348B	Mechanically compatible with	2.92 & 3.5										
Interface																	
Standard	MIL-STD-348B																
Mechanically compatible with	2.92 & 3.5																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 604 531 656" style="border: 1px solid black;">Electrical Data</td> </tr> <tr> <td data-bbox="129 663 774 698">Impedance</td> <td data-bbox="774 663 1481 698">50Ω</td> </tr> <tr> <td data-bbox="129 710 774 745">Frequency Range</td> <td data-bbox="774 710 1481 745">DC To 18GHz</td> </tr> <tr> <td data-bbox="129 757 774 792">VSWR</td> <td data-bbox="774 757 1481 792">≤ 1.2 (DC To 18GHz)</td> </tr> <tr> <td data-bbox="129 804 774 840">Insertion Loss</td> <td data-bbox="774 804 1481 840">≤ 0.04 x √f(GHz) dB</td> </tr> <tr> <td data-bbox="129 851 774 887">Insulation Resistance</td> <td data-bbox="774 851 1481 887">≥ 5000MΩ</td> </tr> <tr> <td data-bbox="129 898 774 934">Dielectric Withstanding Voltage (at sea level)</td> <td data-bbox="774 898 1481 934">1500 V rms</td> </tr> <tr> <td data-bbox="129 945 774 981">Working Voltage (at sea level)</td> <td data-bbox="774 945 1481 981">500 V rms</td> </tr> </table>		Electrical Data		Impedance	50Ω	Frequency Range	DC To 18GHz	VSWR	≤ 1.2 (DC To 18GHz)	Insertion Loss	≤ 0.04 x √f(GHz) dB	Insulation Resistance	≥ 5000MΩ	Dielectric Withstanding Voltage (at sea level)	1500 V rms	Working Voltage (at sea level)	500 V rms
Electrical Data																	
Impedance	50Ω																
Frequency Range	DC To 18GHz																
VSWR	≤ 1.2 (DC To 18GHz)																
Insertion Loss	≤ 0.04 x √f(GHz) dB																
Insulation Resistance	≥ 5000MΩ																
Dielectric Withstanding Voltage (at sea level)	1500 V rms																
Working Voltage (at sea level)	500 V rms																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 1102 531 1153" style="border: 1px solid black;">Mechanical Data</td> </tr> <tr> <td data-bbox="129 1160 774 1196">Recommended Coupling Nut Torque</td> <td data-bbox="774 1160 1481 1196">7 to 9.5 in-lbs</td> </tr> <tr> <td data-bbox="129 1207 774 1243">Coupling Proof Torque</td> <td data-bbox="774 1207 1481 1243">15 in-lbs</td> </tr> <tr> <td data-bbox="129 1254 774 1290">Coupling Nut Retention Force</td> <td data-bbox="774 1254 1481 1290">≥ 60.7 lbs</td> </tr> <tr> <td data-bbox="129 1301 774 1337">Contact Captivation-axial</td> <td data-bbox="774 1301 1481 1337">≥ 6.1 lbs</td> </tr> <tr> <td data-bbox="129 1348 774 1384">Durability (mating)</td> <td data-bbox="774 1348 1481 1384">≥ 500</td> </tr> </table>		Mechanical Data		Recommended Coupling Nut Torque	7 to 9.5 in-lbs	Coupling Proof Torque	15 in-lbs	Coupling Nut Retention Force	≥ 60.7 lbs	Contact Captivation-axial	≥ 6.1 lbs	Durability (mating)	≥ 500				
Mechanical Data																	
Recommended Coupling Nut Torque	7 to 9.5 in-lbs																
Coupling Proof Torque	15 in-lbs																
Coupling Nut Retention Force	≥ 60.7 lbs																
Contact Captivation-axial	≥ 6.1 lbs																
Durability (mating)	≥ 500																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 1503 531 1554" style="border: 1px solid black;">Environmental Data</td> </tr> <tr> <td data-bbox="129 1561 774 1597">Temperature Range</td> <td data-bbox="774 1561 1481 1597">-65°C to +165°C</td> </tr> <tr> <td data-bbox="129 1608 774 1644">Thermal Shock</td> <td data-bbox="774 1608 1481 1644">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="129 1655 774 1691">Moisture Resistance</td> <td data-bbox="774 1655 1481 1691">MIL-STD-202, Method 206</td> </tr> <tr> <td data-bbox="129 1702 774 1738">Corrosion</td> <td data-bbox="774 1702 1481 1738">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="129 1749 774 1785">RoHS</td> <td data-bbox="774 1749 1481 1785">Compliant</td> </tr> </table>		Environmental Data		Temperature Range	-65°C to +165°C	Thermal Shock	MIL-STD-202, Method 107, Condition B	Moisture Resistance	MIL-STD-202, Method 206	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant				
Environmental Data																	
Temperature Range	-65°C to +165°C																
Thermal Shock	MIL-STD-202, Method 107, Condition B																
Moisture Resistance	MIL-STD-202, Method 206																
Corrosion	MIL-STD-202, Method 101, Condition B																
RoHS	Compliant																

ADS-A3A8

