

# Miniature Slide Switches


## Specifications:

Contact rating:	30 V DC, 350 mA
Contact resistance:	< 20 mΩ
Insulation resistance:	> 100 MΩ at 500 V DC
Dielectric strength:	500 V, 50 Hz for the duration of 1 minute
Operating temperature:	-20 °C to +85 °C
Mechanical life:	minimum 10 000 operations
Contacts:	copper alloy, silver-plated over nickel barrier
Contact timing:	shorting (non-shorting only if specified)
Slide colour:	black, further colours on request
Soldering conditions:	wave-soldering – max.: 5 sec, 260 °C ± 5 °C


<b>Models:</b>	Operating positions		Length (mm)	
			A	B

MFP 1220  
MFP 1320  
MFP 1420  
MFP 1520  
MFP 1620

2  
3  
4  
5  
6




13.0 7.5  
15.5 10.0  
18.0 12.5  
20.5 15.0  
23.0 17.5




MFP 1220 – R  
MFP 1320 – R  
MFP 1420 – R  
MFP 1520 – R  
MFP 1620 – R

2  
3  
4  
5  
6




13.0 7.5  
15.5 10.0  
18.0 12.5  
20.5 15.0  
23.0 17.5




MFP 1323  
MFP 1424

3  
4



15.5 10.0  
18.0 12.5



MFP 1323 – R  
MFP 1424 – R

3  
4



15.5 10.0  
18.0 12.5

