



229917-1

PICABOND® Connector, 1000 strip, 48 Vdc, yellow

- Lightweight, compact, and economical means of splicing multiconductor telephone cable
- No prestripping or cutting required, can tap without service interruptions, eliminates “turndowns”
- Color-coded to indicate size and type of wire; used for butt, straight, bridge and half-tap splicing applications

OBSOLETE

This product was discontinued on: June 1, 2016

Replaced By

229917-2

PICABOND® Connector, 1000 strip, 400 Vdc, yellow

Product Classification

Brand	PICABOND®
Product Series	PICABOND
Product Type	Splice
Regional Availability	Australia/New Zealand EMEA Latin America North America

Body Features

Cable Insulation Material	Air Core PIC Foam Filled PIC
Color Code	Yellow
Sealant	Gel filled

Contact Features

Contact Base Material	Brass
Contact Plating Material	Tin

Dimensions

Wire Size (CMA)	24 – 19 AWG
-----------------	-------------

Electrical Characteristics

Voltage Rating	48 Vdc
----------------	--------

Packaging Features

Packaging Method	Strip
Packaging Quantity	1000

Product Type Features

Splicing Applications	Bridge Butt Full Bridge Half-tap Straight (In-line)
-----------------------	---

229917-1

Usage Conditions

Operating Temperature -40 – 60 °C