



Fiber Optic Power Reducing Build Out Attenuator, singlemode SC/APC 8°, 2dB, green

- Designed to reduce or balance the power in passive optical networks
- Insertable between the connector and the adapter and therefore suited for distribution frames, cabinets and boxes
- High system flexibility because of wave-length independency and polarization insensitivity

OBSOLETE

Replaced By:

C24916-000
OCAB-S2-02-B3

Fiber Optic Power Reducing Build Out Attenuator, singlemode SC/APC 8°, 2dB, green

Product Classification

Regional Availability	EMEA Latin America North America
Product Type	Fiber attenuator
Product Series	OCAB

General Specifications

Interface	SC
Interface Feature	APC

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.652.D
Attenuation Tolerance	± 0.5 dB
Attenuation, nominal	2 dB
Operating Wavelength	1260 – 1360 nm
Optical Power, maximum	250 mW
Return Loss, minimum	65 dB

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
------------------------------	--------------------------------------

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

Regulatory Compliance/Certifications

Agency

CHINA-ROHS

REACH-SVHC

ROHS

Classification

Below maximum concentration value

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant

