

# SHDC-LCC-HP

---

ProPatch® Mini Super High-Density Coax Jacks, LCC, normalling, high-performance, HD

**OBSOLETE**

## Product Classification

<b>Regional Availability</b>	North America
<b>Product Type</b>	Broadcast video connector
<b>Product Brand</b>	Pro Patch®
<b>Product Series</b>	ProPatch

## General Specifications

<b>Body Style</b>	Straight
<b>Inner Contact Attachment Method</b>	Crimp
<b>Interface</b>	LCC female

## Electrical Specifications

<b>Connector Impedance</b>	75 ohm
----------------------------	--------

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +65 °C (-40 °F to +149 °F)
<b>Storage Temperature</b>	-55 °C to +85 °C (-67 °F to +185 °F)
<b>Relative Humidity</b>	0%–95%, non-condensing

## Packaging and Weights

<b>Packaging quantity</b>	1
---------------------------	---

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant/Exempted



