


## PAN-TERM® SPLICES




\*Except BSN22, PS12 and BS22



### BUTT SPLICES



### PARALLEL SPLICES



Insul.	Wire Sizes - AWG					
	26-22	22-18	20-16	14-12	16-14	12-10
<b>BUTT SPLICES</b>						
Nylon	BSN22-C	BSN18-C			BSN14-C	BSN10-L
Vinyl		BSV18X-C			BSV14X-C	BSV10X-L
Non-Ins.	BS22-C	BS18-C			BS14-C	BS10-L
<b>PARALLEL SPLICES</b>						
Nylon		PSN18-C	PSN16-C	PSN12-L		
Non.-Ins.		PS18-C	PS16-C	PS12-L		

## PAN-TERM WIRE JOINTS



LISTED\*  
\*Except JN314-412 and J216-410



CERTIFIED\*



PANDUIT Part Number	Insul. Color	Wire Range		CMA Range		Std. Pkg. Qty.	Bulk Pkg. Qty.
		Min.	Max.	Min.	Max.		
<b>NYLON INSULATED</b>							
JN224-318-C	Red	2#24	2#16	808	5,160	100	1000
JN218-216-C	Clear	2#22	2#16	1,280	5,160	100	1000
JN418-212-C	Clear	4#18	2#12	6,480	14,750	100	1000
JN314-412-C	Clear	3#14	4#12	10,320	26,120	100	1000
<b>NON-INSULATED</b>							
J214-312-T	—	2#14	3#12	5,760	19,590	200	2000
J318-412-T	—	3#18	4#12	4,860	27,330	200	2000
J216-410-L	—	2#16	4#10	5,160	41,600	50	500

## P-CONN™ SCREW-ON WIRE CONNECTORS



### P-CONN™ FAMILY

- High Temperature • PYTHON Nut Style
- HAWK Wing Style
- SIDEWINDER Hex Style
- SHARK Fin Style

HAWK and SHARK Styles Grounding Wire Connector

"Quick-Spin"  
Installation Tools  
(Fits 1/4" Drill)



Part No.	Use With
PQS1	P1, P2
PQS2	P72, P73 P72HT, P73HT
PQS3	P74, P76 P74HT, P76HT
PQS4	PF1, PF2

"Pick-A-P-CONN™"  
Assortment Kits

PANDUIT Part Number	Description—Kit Includes:
KP-305	1 - Reusable plastic box 100 - Yellow P1 100 - Orange P73 75 - Red P2 15 - Blue P4 2 - Quick Spins
KP-305S	1 - Reusable plastic box 100 - Yellow PF1 100 - Orange P73 75 - Red PF2 15 - Blue PF4 2 - Quick Spins

\*For Bulk Pkg. Qty. - contact distributor.

PANDUIT Part Number	Insul. Color	Wire Range		CMA Range		Std. Pkg. Qty.	Bulk Pkg. Qty.
		Min.	Max.	Min.	Max.		
<b>NYLON INSULATED — SIDEWINDER™ HEX STYLE</b>							
PH1-C PH1-D	Tan	(3) #22	(5) #12	1,920	35,250	100	500
PH2-L PH2-TL	Gray	(1) #12 (1) #14	(2) #8 (2) #12	9,060	46,080	50	250
<b>NYLON INSULATED — SHARK™ FIN STYLE</b>							
PF1-C PF1-D	Yellow	(4) #22	(3) #12	3,560	19,590	100 —	— 500
PF2-C PF2-D	Red	(3) #22	(5) #12	1,920	32,650	100 —	— 500
PF4-L PF4-TL	Blue	(1) #14 & (1) #12	(5) #10	10,640	51,600	50 —	— 250
<b>GROUNDING WIRE CONNECTOR — SHARK™ FIN STYLE</b>							
PF2G-C PF2G-D	Green	(2) #14	(3) #12	8,220	32,650	100	500
<b>NYLON INSULATED — HAWK™ WING STYLE</b>							
P1-C P1-D	Yellow	(3) #22	(3) #12	2,560	19,590	100 —	— 500
P2-C P2-D	Red	(3) #22	(3) #12 & (1) #8	3,200	36,100	100 —	— 500
P4-L P4-TL	Blue	(1) #12 & (1) #14	(2) #6 & (1) #10	10,640	62,860	50 —	— 250
<b>GROUNDING WIRE CONNECTOR — HAWK™ WING STYLE</b>							
P2G-C P2G-D	Green	(2) #14	(5) #12	8,220	32,650	100 —	— 500
<b>NYLON INSULATED — PYTHON™ NUT STYLE*</b>							
P72-C P72-D	Blue	(2) #22	(3) #16	1,280	7,740	100 —	— 500
P73-C P73-D	Orange	(3) #20	(4) #16	3,060	10,320	100 —	— 500
P74-C P74-D	Yellow	(2) #18	(3) #12	3,240	19,590	100 —	— 500
P76-C P76-TL	Red	(4) #18	(4) #12	6,480	26,120	100 —	— 250
<b>HIGH TEMPERATURE — PYTHON™ NUT STYLE*</b>							
P72HT-D	Black	(2) #22	(3) #16	1,280	7,740	—	500
P73HT-D		(3) #20	(4) #16	3,060	10,320	—	500
P74HT-D		(2) #18	(3) #12	3,240	19,590	—	500
P76HT-TL		(4) #18	(4) #12	6,480	26,120	—	250