



SAW multimedia filters

Series/Type: M3565M

The following products presented in this data sheet are being withdrawn.

Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B39458M3565M201		2011-01-14	2011-09-30	2012-09-30

For further information please contact your nearest EPCOS sales office, which will also support you in selecting a suitable substitute. The addresses of our worldwide sales network are presented at www.epcos.com/sales.

SAW Components

M 3565 M

IF Filter for Quasi/Split Sound Applications

45,75 MHz

Data Sheet

Standard

Plastic package SIP5K


■ M/N

Features

- TV IF filter for quasi/split sound applications (separate picture and sound channel)
- Picture channel with Nyquist slope and sound suppression, symmetrical output
- High color carrier
- Constant group delay
- Sound channel with pass band for sound carrier only

Terminals


■ Tinned CuFe alloy



Dimensions in mm, approx. weight 1,0 g

Pin configuration

- 1 Input
- 2 Chip carrier - ground
- 3 Output - sound
- 4 Output - picture
- 5 Output - picture



Type	Ordering code	Marking and package according to	Packing according to
M 3565 M	B39458-M3565-M201	C61157-A1-A15	F61074-V8067-Z000

Maximum ratings

Operating temperature range	T_A	-25/+65	°C	
Storage temperature range	T_{stg}	-40/+85	°C	
DC voltage	V_{DC}	5	V	between any terminals
AC voltage	V_{pp}	10	V	between any terminals

SAW Components
M 3565 M
IF Filter for Quasi/Split Sound Applications
45,75 MHz
Data Sheet
Characteristics of picture channel



Reference temperature: $T_A = 25 (45) ^\circ \text{C}$
Terminating source impedance: $Z_S = 50 \Omega$
Terminating load impedance: $Z_L = 2 \text{ k}\Omega \parallel 3 \text{ pF}$



		min.	typ.	max.	
Insertion attenuation	α				
Reference level for the following data	44,06 (44,00) MHz	13,8	15,3	16,8	dB
Relative attenuation	α_{rel}				
Picture carrier	45,81 (45,75) MHz	5,1	6,1	7,1	dB
Color carrier	42,23 (42,17) MHz	-1,3	-0,3	0,7	dB
	42,06 (42,00) MHz	—	-0,2	—	dB
Sound carrier	41,31 (41,25) MHz	24,0	38,0	—	dB
Adjacent picture carrier	39,81 (39,75) MHz	45,0	58,0	—	dB
Adjacent sound carrier	47,31 (47,25) MHz	42,0	53,0	—	dB
Lower sidelobe	35,06 ... 39,81 (35,00 ... 39,75) MHz	40,0	45,0	—	dB
Upper sidelobe	47,31 ... 55,06 (47,25 ... 55,00) MHz	35,0	39,0	—	dB
Reflected wave signal suppression					
1,2 μs ... 6,0 μs after main pulse (test pulse 250 ns, carrier frequency 44,06 MHz)		42,0	52,0	—	dB
Feedthrough signal suppression					
1,3 μs ... 1,2 μs before main pulse (test pulse 250 ns, carrier frequency 44,06 MHz)		50,0	56,0	—	dB
Group delay ripple (p-p)	$\Delta\tau$	—	50	—	ns
Impedance at 44,06 MHz					
Input: $Z_{\text{IN}} = R_{\text{IN}} \parallel C_{\text{IN}}$		—	1,1 $\parallel$ 18,7	—	k Ω $\parallel$ pF
Output: $Z_{\text{OUT}} = R_{\text{OUT}} \parallel C_{\text{OUT}}$		—	1,9 $\parallel$ 2,8	—	k Ω $\parallel$ pF
Temperature coefficient of frequency	TC_f	—	-72	—	ppm/K


SAW Components
M 3565 M
IF Filter for Quasi/Split Sound Applications
45,75 MHz
Data Sheet
Characteristics of sound channel

Reference temperature: $T_A = 25 (45) ^\circ \text{C}$
Terminating source impedance: $Z_S = 50 \Omega$
Terminating load impedance: $Z_L = 2 \text{ k}\Omega \parallel 3 \text{ pF}$

		min.	typ.	max.	
Insertion attenuation	α				
Reference level for the following data	41,31 (41,25) MHz	9,1	10,6	12,1	dB
Relative attenuation	α_{rel}				
Picture carrier	45,81 (45,75) MHz	38,0	44,0	—	dB
Color carrier	42,23 (42,17) MHz	25,0	35,0	—	dB
Adjacent picture carrier	39,81 (39,75) MHz	38,0	44,0	—	dB
Adjacent sound carrier	47,31 (47,25) MHz	42,0	50,0	—	dB
Lower sidelobe	35,06 ... 39,81 (35,00 ... 39,75) MHz	37,0	42,0	—	dB
Upper sidelobe	47,31 ... 55,06 (47,25 ... 55,00) MHz	37,0	43,0	—	dB
Impedance at 41,31 MHz					
Input: $Z_{\text{IN}} = R_{\text{IN}} \parallel C_{\text{IN}}$		—	0,7 $\parallel$ 19,5	—	k Ω $\parallel$ pF
Output: $Z_{\text{OUT}} = R_{\text{OUT}} \parallel C_{\text{OUT}}$		—	1,2 $\parallel$ 2,7	—	k Ω $\parallel$ pF
Temperature coefficient of frequency	TC_f	—	-72	—	ppm/K

SAW Components
M 3565 M
IF Filter for Quasi/Split Sound Applications
45,75 MHz
Data Sheet
Frequency response of picture channel


SAW Components
M 3565 M
IF Filter for Quasi/Split Sound Applications
45,75 MHz
Data Sheet
Frequency response of picture channel

Time domain response of picture channel


Data Sheet
Frequency response of sound channel


SAW Components**M 3565 M****IF Filter for Quasi/Split Sound Applications****45,75 MHz****Data Sheet****Published by EPCOS AG****Surface Acoustic Wave Components Division, SAW CE MM PD****P.O. Box 80 17 09, D-81617 München**

© EPCOS AG 2001. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.