

E-Series 3-Way 0° Power Divider

5 - 500 MHz

ESSM-3-1W

V3.00

Features

- 3 Way
- 0°
- Surface Mount

Specifications @ 25°C

Frequency Range		5 - 500 MHz	
Insertion Loss	Typical	Maximum	
	5 - 50 MHz	0.4 dB	0.8 dB
	50 - 250 MHz	0.6 dB	1.4 dB
	250 - 500 MHz	1 dB	1.75 dB
Isolation	Typical	Minimum	
	5 - 50 MHz	25 dB	20 dB
	50 - 250 MHz	22 dB	15 dB
	250 - 500 MHz	18 dB	15 dB
Amplitude Unbalance		Maximum	
5 - 50 MHz		0.1 dB	
50 - 250 MHz		0.4 dB	
250 - 500 MHz		0.9 dB	
Phase Unbalance		Maximum	
5 - 50 MHz		2°	
50 - 250 MHz		3°	
250 - 500 MHz		6°	

Operating Characteristics

Impedance	50 Ohms Nominal
-----------	-----------------


Ordering Information

Part No.	Packaging
ESSM-3-1W	Tube
ESSM-3-1WTR	Forward Tape & Reel

Absolute Maximum Ratings

Parameter	Absolute Maximum
Maximum Power Rating	1 Watt
Internal Load Dissipation	0.125 Watt
Pin Temp (10 sec)	260°C
Storage Temperature	-55°C to 100°C

SM-4



Dimensions in () are in mm.
 Unless Otherwise Noted: .x = ±0.04 (1.00)
 .xx = ±0.02 (0.50)
 .xxx = ±0.010 (0.250)

Pin Configuration

Function	Pin No.
Ground	2,3,6,7
Input	8
Port 1	5
Port 2	4
Port 3	1

S 1111 D