



Fig. 1

- Unique compliant tail pins conform to the plated thru-hole without stressing the inner layers of a multilayer board.
- Recommended plated thru-hole for 304 series: .036"-.041" use a 1.1mm drill prior to plating. Using M-M# 0477 & 0478 pins.
- For 346 series: .040"±.003" finished plated thru-hole. using M-M# 4612 & 4613 pins. Patent No. 4,799,904.
- Hi-Rel, 4-finger BeCu #30 clip rated at 3 amps. See page 208 for details.



Ordering Information

Series 304...770 SOLDERLESS PRESS-FIT

Fig. 1	(For .062" Thick Boards)
	304-13-1__-41-770 Specify # of pins → 01-64

Series 304...780 SOLDERLESS PRESS-FIT

Fig. 2	(For .125" Thick Boards)
	304-13-1__-41-780 Specify # of pins → 01-64

Series 304...770 and 304...780 are available in plating code 13 only.

Series 346...012 COMPLIANT SOLDERLESS PRESS-FIT

Fig. 3	(For .060-.100" Thick Boards)
	346-XX-1__-41-012 Specify # of pins → 01-64

Series 346...013 COMPLIANT SOLDERLESS PRESS-FIT

Fig. 4	(For .090-.130" Thick Boards)
	346-XX-1__-41-013 Specify # of pins → 01-64

*XX= Plating Code
See Below*

SPECIFY PLATING CODE XX=	13	93	99
Sleeve (Pin)	10μ" Au	200μ" Sn/Pb	200μ" Sn/Pb
Contact (Clip)	30μ" Au	30μ" Au	200μ" Sn/Pb