



NOTES:

1. UL LISTED AND CSA CERTIFIED FOR:
  - A. 600V MAX VOLTAGE RATING
  - B. 221° F (105 C) MAX TEMP. RATING (CSA)
  - C. 257° F (125°C) MAX TEMP. RATING (UL)
  - D. STRANDED COPPER WIRE ONLY.
2. MATERIAL:
  - A. STAMPING- BRASS, NICKEL PLATED  
- COPPER, NICKEL PLATED (FOR DNF10-250FIMB)
  - B. HOUSING-TYPE 6/6 NYLON
3. DIMENSIONS IN BRACKETS ARE IN mm OR mm<sup>2</sup>
4. COLORS ARE TRANSLUCENT
5. PACKAGE QTY. -L=50  
-D=500
6. WIRE STRIP LENGTH:  $9/32^{+1/32}_0$  (7.1<sup>+0.8</sup><sub>-0</sub>)  
 $3/8^{+1/32}_0$  (9.5<sup>+0.8</sup><sub>-0</sub>)  
(FOR DNF10-250FIMB)



LISTED  
20H3  
E78522



CERTIFIED\*  
LR31212

\* DNF10-250FIMB IS NOT CSA CERTIFIED

PART NUMBER	TAB SIZE	WIRE RANGE AWG (mm <sup>2</sup> )	COLOR (note 4)	MAX. INSUL.	DIMENSIONS in			CRIMP TOOLS
					A ±.03	B ±.01	C ±.01	
DNF18-250FIMB	.250 X .032 (6,3 X 0,8)	22-18 (,5-1,0)	RED	.136 (3,45)	.91 (23,1)	.45 (11,4)	.34 (8,6)	CT-520 CT-1525
DNF14-250FIMB	.250 X .032 (6,3 X 0,8)	16-14 (1,5-2,5)	BLUE	.160 (4,06)	.91 (23,1)	.45 (11,4)	.34 (8,6)	
DNF10-250FIMB	.250 X 0.32 (6,3 X 0,8)	12-10 (4,0-6,0)	YELLOW	.220 (5,59)	.96 (24,4)	.45 (11,4)	.36 (9,1)	CT-1550 CT-1551

REV	DATE	BY	CHK	DESCRIPTION	ECN #	CUST	PM
08	7/03	KLFU		UPDATED DRAWING			
07	1/02	SAB	SKB	DNF10-250FIMB WAS NOT UL LISTED	09821	JAC	TRO
06	1/01	RM	SKB	THE FILESPEC WAS N41402AA_PCD_05	08925	SKB	CH
05	9/00	EJS	SKB	ADD PART DNF10-250FIMB UPDATED NOTES AND DRAWING	08721	SKB	CH
04	10/98	JKD	SKB	MATERIAL WAS TIN PLATED	07642	JW	TO

A41402\_08



TINLEY PARK, ILLINOIS

LOOSE PC. FULLY INSULATED UNI-MALE DISCONNECT  
.250 X .032

DRAWN BY	JV	CHK'D		SCALE		DRAWING NO.	A41402
----------	----	-------	--	-------	--	-------------	--------