

General Information

Extended Product Type:	DS254N-UC-K16/0,03
Product ID:	2CDR274568R1167
EAN:	4016779907798
Catalog Description:	DS254N-UC-K16/0,03 DC-Railway RCBO 10kA,4P/N-UC,B type,K 16A,30mA
Long Description:	DS254N-UC-K16/0,03 DC-Railway RCBO 10kA,4P/N-UC,B type,K 16A,30mA

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Residual Current Devices RCDs » Residual Current Circuit Breakers with Overcurrent Protection RCBO

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362010

Dimensions

Product Net Width:	105 mm
Product Net Height:	69 mm
Product Net Depth:	157.5 mm
Product Net Weight:	1.1 kg

Technical

Tripping Characteristic:	K
Rated Current (I_n):	16 A
Number of Poles:	4
Rated Short-Circuit Capacity (I_{cn}):	10 kA (AC) kA (DC) 10 kA
Power Loss:	6,3 W

Environmental

Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +70 °C
--------------------------	--

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CDK420022D2702
---------------------------------	-----------------

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	110 mm
Package Level 1 Height:	85 mm
Package Level 1 Length:	165 mm
Package Level 1 Gross Weight:	1.1 kg
Package Level 1 EAN:	4016779908238

Classifications

ETIM 5:	EC000905 - Earth leakage circuit breaker
ETIM 6:	EC000905 - Earth leakage circuit breaker
eClass:	7.0 27142207
UNSPSC:	39121614

