




.250 Quick-Connect Series Flag Type




— Cross Bridge Design —
To Accept .250 x .032 Male Tab

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	20-16	None	✓ ✓	1250	1 3/32 ± 1/32	.018	Pre Tinned Brass	3000H 405A-4
							Brass	3000H 405AB-4
							Silver Plated Brass	3000H 405AC-4
	16-12	None	✓ ✓	1250	1 3/32 ± 1/32	.018	Pre Tinned Brass	3000H 405A
							Brass	3000H 405AB
							Silver Plated Brass	3000H 405AC
	16-12	None	✓ ✓	3000	1 3/32 ± 1/32	.018	Pre Tinned Brass	3000H 407A*
							Brass	3000H 407AB*
							Silver Plated Brass	3000H 407AC*
							Pre Tinned Phos. Bronze	3000H 407PA*
							Phosphor Bronze	3000H 407PB*
Silver Plated Phos. Bronze	3000H 407PC*							

*Contact factory for special application equipment and pricing information.

.250 Quick-Connect Series Flag Type

— Axial Bridge Design —
To Accept .250 x .032 Male Tab

STYLE AND DIMENSIONS	WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	20-14	.075-.155	✓ ✓	4000	7/32 ± 1/32	.020	Pre Tinned Brass	3000H 49A
							Brass	3000H 49AB
							Silver Plated Brass	3000H 49T
							Pre Tinned Phos. Bronze	3000H 49U
							Phos. Bronze	3000H 49UB
	20-14	.075-.175	✓ ✓	4000	7/32 ± 1/32	.020	Pre Tinned Brass	3000H 45A
							Brass	3000H 45AB
							Silver Plated Brass	3000H 45AC
							Pre Tinned Phos. Bronze	3000H 45C
	20-14	None	✓ ✓	5000	1 1/32 ± 1/32	.020	Pre Tinned Brass	3000H 4A
							Brass	3000H 4AB
							Silver Plated Brass	3000H 4AC
	20-14	None	✓ ✓	4000	1 1/32 ± 1/32	.020	Tin Lead Brass	3000H 4ATL
							Pre Tinned Brass	3000H 400A*
							Brass	3000H 400AB*

*Recommended for Application with CS-21 Auto Connect System.