



This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

4112_9311

CREATION				
PEN: /				
NOM: LEGENDRE T.				
DATE: August 14, 2007				
APPR.: BROCHET L.				
	Issue	Revisions	Name	Approved

MATERIAL:

- SHELL : DIE CAST ALUMINUM ALLOY PER SAE AMS-QQ-A-591
- INSERT RETENTION PLATES : ALUMINUM ALLOY PER SAE AMS-QQ-A-250
- POLARIZING RETENTION PLATE : ALUMINUM ALLOY PER SAE AMS-QQ-A-250
- POLARIZING POST : ZINC ALLOY PER ASTM B 86
- INSERTS : REINFORCED EPOXY RESIN PER ASTM D 5948 OR HIGH GRADE THERMOPLASTIC
- C4 INSERTS : FRONT PLATE : THERMOPLASTIC PER ASTM D 4067
REAR PLATE : STAINLESS STEEL PER ASTM A 582
- GROMMETS AND O'RING SEALS : FLUOROSILICONE PER SAE AMS-R-25988
- CONTACT RETENTION CLIPS : BERYLLIUM COPPER PER ASTM B 194
- COVER : THERMOPLASTIC ELASTOMER
- SCREWS AND WASHERS : CORROSION RESISTANT MATERIAL

FINISH:

- SHELL : CHROMATATION PER MIL-C-5541, CLASS 3
- INSERT RETENTION PLATES : BLUE ANODIZED PER MIL-A-8625
- POLARIZING RETENTION PLATE : CHROMATATION PER MIL-C-5541, CLASS 3
- POLARIZING POST : ELECTROLESS NICKEL PER SAE AMS-2404

NOTES:

- INSERT LAYOUT :
 - CAVITY A : C4 FOR FRONT RELEASE, REAR REMOVABLE COAX CONTACTS
 - CAVITY B : 60 FOR REAR RELEASE, REAR REMOVABLE POWER CONTACTS
 - CAVITY C : 59 FOR REAR RELEASE, REAR REMOVABLE SIGNAL AND POWER CONTACTS
- CONNECTOR SUPPLIED WITHOUT CONTACT
- CONNECTOR SUPPLIED WITH:
COVER P/N : 620 995 005 & 620 995 006 (INSTALLED)
- MARKING : CONNECTOR AND PACKAGING MUST BE MARKED WITH : NSXE2P806X00** + DATE CODE
(CODE ** : SEE NOTE 1 PAGE 1)

4112_9311 This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.