


V23049B1005A222 Product Details



V23049B1005A222
(2-1393256-3)

TE Internal Number: 2-1393256-3



Superseded

[Search for Replacement Parts](#)

Relays with Forcibly Guided Contacts (Safety Relays)

[Not reviewed for RoHS Compliance](#)

Product Highlights:

- Relay Type = Safety Relay SR4
- V23049-B Series
- DC Actuating System
- Contact Arrangement = 2 Form A & 2 Form B, DPST-NO & DPST-NC, 2 N/O & 2 N/C
- Contact Current Rating = 6 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling
---	--

Product Features (Please use the Product Drawing for all design activity)

<p>Product Type Features:</p> <ul style="list-style-type: none"> • Termination Type = Through Hole <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Actuating System = DC • Contact Current Rating (Amps.) = 6 • Coil Resistance (?) = 255 • Coil Power, Nominal (mW) = 0.55 • Input Voltage (VDC) = 12 <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = V23049-B • Polarized = No <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Relay Type = Safety Relay SR4 • Enclosure = Sealed • Contact Type = Single button, forcibly guided • Approx. Dimensions (L x W x H) (mm [in]) = 42.00 x 12.50 x 30.00 [1.654 x .492 x 1.182] • Contact Base Material = Silver Cadmium Oxide, Gold Plated • Number of Bistable Coils = Single • Bistable = No • Mounting Options = PC Board • Approved Standards = UL Recognized, CSA Certified, TUV Approved, VDE Component Mark 	<p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Contact Arrangement = 2 Form A & 2 Form B, DPST-NO & DPST-NC, 2 N/O & 2 N/C • Coil Magnetic System = Monostable <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not reviewed for ELV/RoHS compliance • Lead Free Solder Processes = Not reviewed for lead free solder process <p>Other:</p> <ul style="list-style-type: none"> • Brand = Schrack
--	--

Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)