

MB85281-80/-10/-12

CMOS 4M x 8 NIBBLE MODE DRAM MODULE

The Fujitsu MB85281 is a fully decoded, CMOS dynamic random access memory (DRAM) module consisting of eight MB814101 devices. The MB85281 is optimized for those applications requiring high speed, high performance and large memory storage. The operation and electrical characteristics of the MB85281 are the same as the MB814101 devices which feature nibble mode operation. For ease of memory expansion, the MB85281 is offered in a 30-pad Single In-Line Memory Module (SIMM).

- Organization:
 - 4,194,304 words x 8 bit
- $\overline{\text{RAS}}$ Access time:
 - 80ns max. (MB85281-80)
 - 100ns max. (MB85281-10)
 - 120ns max. (MB85281-12)
- $\overline{\text{CAS}}$ Access Time:
 - 25ns max. (MB85281-80)
 - 30ns max. (MB85281-10)
 - 35ns max. (MB85281-12)
- Nibble Mode Cycle Time:
 - 50ns max. (MB85281-80)
 - 55ns max. (MB85281-10)
 - 60ns max. (MB85281-12)
- Nibble Mode
- Active Power:
 - 3300mW max. (MB85281-80)
 - 2860mW max. (MB85281-10)
 - 2420mW max. (MB85281-12)
- Standby:
 - 44mW max. (CMOS Level)
 - 88mW max. (TTL Level)
- Single +5V Supply $\pm 10\%$ Tolerance
- TTL Compatible I/O
- Decoupling Capacitor:
 - 0.22 μ F, 8pcs
- JEDEC Standard Package Outline:
 - 30-pin SIP (MB85281-XX PL)
 - 30-pad SIMM (MB85281-XX PS)
 - 30-pad SIMM (MB85281-XX PSG)
 - Suffix: PSG (Gold Pad)

ABSOLUTE MAXIMUM RATINGS (See NOTE)

Rating	Symbol	Value	Rating
Supply Voltage	VCC	-1.0 to +7.0	V
Input Voltage	VIN	-1.0 to +7.0	V
Output Voltage	VOUT	-1.0 to +7.0	V
Short Circuit Output Current	IOUT	± 50	mA
Power Dissipation	PD	8.0	W
Storage Temperature	TSTG	-55 to +125	$^{\circ}$ C


NOTE: Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded. Functional operation should be restricted to the conditions as detailed in the operational section of this data sheet. Exposure to absolute maximum rating conditions for extended period may affect device reliability.

PRELIMINARY

PLASTIC PACKAGE
MSS-30P-P06

PLASTIC PACKAGE
MSP-30P-P05

PAD ASSIGNMENT



1

This device contains circuitry to protect the inputs against damage due to high static voltages or electric fields. However, it is advised that normal precautions be taken to avoid application of any voltage higher than maximum rated voltages to this high impedance circuit.

MB85281-80/-10/-12

CAPACITANCE (TA=25°C,f=1MHz)

PARAMETER	SYMBOL	VALUE		UNIT
		Typ	Max	
Input Capacitance, A0-10	CIN1	-	45	pF
Input Capacitance, /RAS	CIN2	-	43	pF
Input Capacitance, /CAS	CIN3	-	39	pF
Input Capacitance, /WE	CIN4	-	45	pF
I/O Capacitance, DQ0-7	CI/O	-	14	pF

DC CHARACTERISTICS

(At recommended operating conditions unless otherwise noted) *

PARAMETER	SYMBOL	CONDITIONS	VALUE			UNIT	NOTE
			Min	Typ	Max		
Output High Level	VOH	IOH= -5mA	2.4	-	-	V	
Output Low Level	VOL	IOL=4.2mA	-	-	0.4	V	
Input Leakage Current	IIL	0V ≤ VIN ≤ 5.5V; 4.5 ≤ VCC ≤ 5.5V VSS=0V; all other pins not under test=0V	-30	-	30	μA	
Output Leakage Current	IOL	0V ≤ VOUT ≤ 5.5V; Data out disabled	-10	-	10	μA	
Operating Current (Average Power Supply Current)	MB85281-80	/RAS & /CAS cycling; tRC=min.	-	-	600	mA	*
	MB85281-10				520		
	MB85281-12				440		
Standby Current (Power Supply Current)	TTL Level	/RAS=/CAS=VIH	-	-	16	mA	
	CMOS Level	/RAS=/CAS ≥ VCC -0.2V			8		
Ref. Current # 1 (Average Power Supply Current)	MB85281-80	/CAS=VIH, /RAS cycling; tRC=min.	-	-	600	mA	*
	MB85281-10				520		
	MB85281-12				440		
Nibble Mode Current	MB85281-80	/RAS=VIL, /CAS cycling tNC=min.	-	-	400	mA	*
	MB85281-10				360		
	MB85281-12				320		
Ref. Current # 2 (Average Power Supply Current)	MB85281-80	/RAS cycling; /CAS - before -/RAS; tRC=min.	-	-	600	mA	*
	MB85281-10				520		
	MB85281-12				440		

* ICC depends on the output load conditions and cycle rate. The specific values are obtained with the output open.

1

MB85281-80/-10/-12

AC CHARACTERISTICS

(At recommended operating conditions otherwise noted.) * Notes 1,2,3

1

PARAMETER	SYM	MB85281-80		MB85281-10		MB85281-12		UNIT	NOTE
		Min	Max	Min	Max	Min	Max		
Time Between Refresh	tREF	-	16.4	-	16.4	-	16.4	ms	
Random Read/Write Cycle Time	tRC	155	-	180	-	210	-	ns	
Access Time From /RAS	tRAC	-	80	-	100	-	120	ns	4,7
Access Time From /CAS	tCAC	-	25	-	30	-	35	ns	5,7
Column Address Access Time	tAA	-	45	-	50	-	60	ns	6,7
Output Hold Time	tOH	5	-	5	-	5	-	ns	
Output Buffer Turn On Delay Time	tON	5	-	5	-	5	-	ns	
Output Buffer Turn Off Delay Time	tOFF	-	25	-	25	-	25	ns	8
Input Transition Time	tT	3	50	3	50	3	50	ns	
/RAS Precharge Time	tRP	65	-	70	-	80	-	ns	
/RAS Pulse Width	tRAS	80	100K	100	100K	120	100K	ns	
/RAS Hold Time	tRSH	25	-	30	-	35	-	ns	
/CAS To /RAS Precharge Time	tCRP	0	-	0	-	0	-	ns	
/RAS To /CAS Delay Time	tRCD	22	55	25	70	25	85	ns	9,10
/CAS Pulse Width	tCAS	25	-	30	-	35	-	ns	
/CAS Hold Time	tCSH	80	-	100	-	120	-	ns	
/CAS Precharge Time(C-B-R Refresh)	tCPN	15	-	15	-	15	-	ns	15
Row Address Setup Time	tASR	0	-	0	-	0	-	ns	
Row Address Hold Time	tRAH	12	-	15	-	15	-	ns	
Column Address Setup Time	tASC	0	-	0	-	0	-	ns	
Column Address Hold Time	tCAH	15	-	15	-	20	-	ns	
RAS to Column Address Delay Time	tRAD	17	35	20	50	20	60	ns	11
Column Address To /RAS Lead Time	tRAL	45	-	50	-	60	-	ns	
Read Command Setup Time	tRCS	0	-	0	-	0	-	ns	
Read Command Hold Time/Reference to /RAS	tRRH	0	-	0	-	0	-	ns	12
Read Command Hold Time/Reference to /CAS	tRCH	0	-	0	-	0	-	ns	12
Write Command Setup Time	tWCS	0	-	0	-	0	-	ns	13
Write Command Hold Time	tWCH	15	-	15	-	20	-	ns	
/WE Pulse Width	tWP	15	-	15	-	20	-	ns	
Write Command To /RAS Lead Time	tRWL	25	-	25	-	30	-	ns	
Write Command To /CAS Lead Time	tCWL	20	-	20	-	25	-	ns	
Data Input Setup Time	tDS	0	-	0	-	0	-	ns	
Data Input Hold Time	tDH	15	-	15	-	20	-	ns	
/RAS Precharge Time to /CAS Active Time Low (Refresh Cycle)	tRPC	0	-	0	-	0	-	ns	
/CAS Set Up Time (For C-B-R Refresh)	tCSR	0	-	0	-	0	-	ns	
/CAS Hold Time (For C-B-R Refresh)	tCHR	15	-	15	-	20	-	ns	

* Refer to MB814101 data sheet electricals for an explanation of notes.

MB85281-80/-10/-12

AC CHARACTERISTICS (Continued)

(At recommended operating conditions otherwise noted.) * Notes 1,2,3

PARAMETER	SYM	MB85281-80		MB85281-10		MB85281-12		UNIT	NOTE
		Min	Max	Min	Max	Min	Max		
Nibble Mode Read/Write Cycle Time	tNC	50	-	55	-	60	-	ns	
Access Time From /CAS Precharge	tNPA	-	45	-	50	-	60	ns	7,14
Nibble Mode /CAS Precharge Time	tNCP	15	-	15	-	15	-	ns	


Notes:

1. An Initial Pause (RAS = CAS = VIH) of 200 μ s is required after power-up followed by any eight RAS - only cycles before proper device operation is achieved. In case of using internal refresh counter, a minimum of eight CAS-before-RAS initialization cycles instead of 8 RAS cycles are required.
2. AC characteristics assume tT = 5nS.
3. VIH (min) and VIL (max) are reference levels for measuring timing of input signals. Also transition times are measured between VIH (min) and VIL (max).
4. Assumes that TRCD < tRCD (max), tRAD < tRAD (max). If tRCD is greater than the maximum recommended value shown in this table, tRAC will be increased by the amount that tRCD exceeds the value shown.
5. If tRCD > tRCD (max), tRAD > tRAD (max), and tASC > tAA - tCAC - tT, access time is tCAC.
6. If tRAD > tRAD (max) and tASC < tAA - tCAC - tT, access time is tAA.
7. Measured with a load equivalent to two TTL loads and 100 pF.
8. tOFF is specified that output buffer changes to high impedance state.
9. Operation within the tRCD (max) limit ensures that tRAC (max) can be met. tRCD (max) is specified as a reference point only; if tRCD is greater than the specific tRCD (max) limit, access time is controlled exclusively by tCAC or tAA.
10. tRCD (min) = tRAH (min) + 2TT + tASC (min).
11. Operation within the tRAD (max) limit ensures that tRAC (max) can be met. tRAD (max) is specified as a reference point only; if tRAD is greater than the specified tRAD (max) limit, access time is controlled exclusively by tCAC or tAA.
12. Either tRRH or tRCH must be satisfied for a read cycle.
13. tWCS must be satisfied for a write cycle.
14. tNPA is access time from the selection of a new column address (that is caused by changing CAS from "L" to "H"). Therefore, if tCP is long, tCPA is longer than tCPA (max).
15. Assumes CAS - before - RAS refresh.

1

MB85281-80/-10/-12

FUNCTIONAL BLOCK DIAGRAM



1

PACKAGE DIMENSIONS

