



Our years of experience translates to immediate support for existing or new project development. Continued commitment to technological advancement assures our customers access to the latest developments available.

N Series



Applications:

Transmitters and Receivers, Broadcast Equipment, Antenna, LANs, Test and Measurement

*Electrical Specifications:

Voltage Rating:	AC 500V
Withstanding Voltage:	AC 1000V one minute
Insulation Resistance:	1000 M Ω min at DC 500V
Contact Resistance:	3 m Ω max at DC 1A
VSWR:	1.2 max 0-4 GHz
Frequency Range:	0-4000 MHz
Impedance:	50 Ohm

DIN 7/16 Series



Applications:

Broadcast Communications, Control Components, Cellular Base Stations, Jumper Cables

*Electrical Specifications:

Voltage Rating:	2.7 kV RMS
Withstanding Voltage:	4 kV RMS
Insulation Resistance:	10 G Ω min
Contact Resistance:	8 m Ω After Conditioning
VSWR:	1.02 max 0-7 GHz
Frequency Range:	DC-7 GHz
Impedance:	50 Ohm

UHF Series



Applications:

CB Radios, Antennas, Public Address Systems, Landing Systems, Ground Control Apparatus

*Electrical Specifications:

Voltage Rating:	AC 500V
Withstanding Voltage:	AC 1000V one minute
Insulation Resistance:	1000 M Ω min at DC 500V
Contact Resistance:	3 m Ω max at DC 1A
Frequency Range:	0-300 MHz
Impedance:	Non-Constant

**These characteristics are typical and may not apply to all connectors*