



CIRCUIT PROTECTION

RADIAL-LEADED DEVICES



✓ Active

TE CONNECTIVITY (TE)

RGEF400

Raychem | PolySwitch Devices , PPTC , RGEF

RGEF400

TE Internal Number: RF3203-000

Always EU RoHS/ELV Compliant

Hold Current (Room Temperature) (A) **4**

Voltage (Max) (V) **16**

Current (Max) (A) **100**

Lead Type **Straight**

Trip Current (Room Temperature) (A) **6.8**

Catalog Pages/Data Sheets

CATALOG PAGES FOR POLYSWITCH RADIAL

PDF
English

Product Specifications

Product Specification

RGEF400

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Product Type

PolySwitch Resettable Devices

Electrical Characteristics

Hold Current (Room Temperature) (A)	4
Voltage (Max) (V)	16
Current (Max) (A)	100
Trip Current (Room Temperature) (A)	6.8
Resistance (Min) (Ω)	.021
Resistance (Max) (Ω)	.039
Resistance (Max) (20°C, 1-Hr Post Trip) (Ω)	.06
Time to Trip (Max) (seconds)	1.7
Power Dissipation (Typical) (W)	2.4



Body Features

Lead Type

Straight

Lead Spacing (mm)

5.08

Lead spacing (mm)

3.03

Coating

Coated

Termination Features

Construction

Radial-Leaded

Usage Conditions

Operating Temperature (Max) (°C)

85

Industry Standards

CSA File Number

CA78165

TUV Certificate Number

Available on Request (per IEC 60730-1)

UL File Number

E74889

Packaging Features

Packaging Method





Bag

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD HEADERS & RECEPTACLES	RECTANGULAR POWER CONNECTORS	CRIMP RINGS & SPADES	RADIAL-LEADED DEVICES
			
03P MTA100 CONN ASSY F/T 24AWG 3-644563-3	08P MTA156 HDR ASSY FL ST LF 3-641208-8	RING 190(4.82 MM) TERMINAL 18-14 AWG BR 40661	RGEF300 RGEF300
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products