




Small Signal Diodes



**SOD80
Mini Melf**

Type	miniReel Order Number	 4"	miniBag Order Number		Ratings				
					VOLT PIV	CURRENT MAX	POWER @25°C	Rev. Recovery Time	Tj max °C
Switching type, General Purpose									
BAV100	70-0100	<i>500 pc. Reel</i>	50-0100	<i>100 pc. Bag</i>	60V	200mA	500mW	50nS	175°C
BAV101	70-0101		50-0101		120V	200mA	500mW	50nS	175°C
BAV102	70-0102		50-0102		200V	200mA	500mW	50nS	175°C
BAV103	70-0103		50-0103		250V	200mA	500mW	50nS	175°C
LL914	70-0914	<i>500 pc. Reel</i>	50-0914	<i>100 pc. Bag</i>	75V	250mA	500mW	4.0nS	175°C
LL4148	70-4148		50-4148		100V	200mA	500mW	4.0nS	175°C
LL4150	70-4150		50-4150		50V	200mA	500mW	4.0nS	175°C
LL4151	70-4151		50-4151		75V	150mA	500mW	2.0nS	175°C
LL4154	70-4154		50-4154		35V	150mA	500mW	2.0nS	175°C
LL4448	70-4448		50-4448		100V	150mA	500mW	4.0nS	175°C
Schottky Diode									
LL101A	70-1011	<i>500 pc. Reel</i>	50-1011	<i>100 pc. Bag</i>	60V	10mA	400mW	1.0nS	125°C
LL101B	70-1012		50-1012		50V	10mA	400mW	1.0nS	125°C
LL101C	70-1013		50-1013		40V	10mA	400mW	1.0nS	125°C
LL103A	70-1031	<i>500 pc. Reel</i>	50-1031	<i>100 pc. Bag</i>	40V	200mA	400mW	10nS	125°C
LL103B	70-1032		50-1032		30V	200mA	400mW	10nS	125°C
LL103C	70-1033		50-1033		20V	20mA	400mW	10nS	125°C

Specifications

Case: LL34/SOD80

ø 1.5mm x 3.5mm
miniMelf

Cathode Band



When a few will do 