



Preliminary Specification
of
1.55 μ m MQW-FP Laser Diode
with Aspherical Lens Cap

SLT1330 Series



1. General

SLT1330 Series are 1.55 μ m InGaAsP/InP MQW-FP laser diodes fabricated by OMVPE entirely. These diodes have low threshold current and high performance at high temperature.

A laser diode is mounted into a coaxial package integrated with an InGaAs monitor PD and an aspherical lens cap.

2. Package dimension and pin assignment

(See attached appendix.)

3. Absolute maximum ratings

Parameter	Symbol	Ratings	Unit
Storage temperature	Tstg	-40~+100	°C
Operating case temperature	Top	-40~+85	°C
Peak optical output power	Po	20	mW
Forward current (LD)	IfL	150	mA
Reverse voltage (LD)	VrL	2	V
Reverse voltage (PD)	VrP	15	V
Reverse current (PD)	IrP	2	mA
Soldering temperature (<10s)	Stemp	260	°C

4. Electrical and optical characteristics (Po=5mW, Tc=+25°C, unless otherwise noted.)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Threshold current	I _{th}	CW	—	8	15	mA
Optical output power	P _o	CW, I _f =I _{th} +20mA	3.0	5.0	—	mW
Operating voltage	V _f	CW	—	1.2	1.6	V
Slope efficiency	Se	CW	0.15	—	—	mW/mA
Central wavelength	λ _c	CW	1520	1550	1580	nm
Spectral width	Δλ	CW, RMS	—	—	5	nm
Rise time	t _r	I _b =I _{th} , 20-80%	—	—	0.5	ns
Fall time	t _f	I _b =I _{th} , 80-20%	—	—	0.5	ns
Monitor current	I _m	CW, V _{rP} =5V	200	—	—	μA
Monitor dark current	I _d	V _{rP} =5V	—	—	10	nA
Monitor capacitance	C	V _{rP} =5V, f=1MHz	—	—	10	pF

Preliminary

5. Ordering information

Part number	Pin assignment	Number of pin	Pin length
SLT1330	Type A	4	13.5±0.5mm
SLT1336	Type C	4	13.5±0.5mm

6. Precaution

- (1) Radiation emitted by laser devices can be dangerous to the eyes. Avoid eye or skin exposure to direct or scattered radiation.
- (2) The laser diodes should be handled in the same manner as ordinary semiconductor devices to prevent the electro-static damages. For safe keeping and carrying, the modules should be packaged with ESD proof material. To assemble the modules on PCB, the workbench, the soldering iron and the human body should be grounded.
- (3) Please pay special attention to the atmosphere condition because the dew on the module may cause some electrical damages.
- (4) Under such a strong vibration environment as in automobile, the performance and reliability are not guaranteed.

Preliminary

Appendix

Part No.: SLT1330□/□□□

(Customize code)


Code	Pin assignment	Pin length (L1)
0	Type A	13.5±0.5
6	Type C	13.5±0.5

Pin No.	Pin function for typeA
1	LD anode (CASE)
2	LD cathode
3	PD cathode
4	PD anode

Pin No.	Pin function for typeB
1	LD anode (CASE)
2	PD anode
3	PD cathode
4	LD cathode

Pin No.	Pin function for typeC
1	(CASE)
2	LD cathode
3	PD anode
4	LD anode/PD cathode

Pin Assignment



Unit: mm

7. For More Information

U.S.A.

ExceLight Communications Inc.

4021 Stirrup Creek Drive, Suite 200, Durham NC, 27703

U.S.A.

Tel. (919) 361-1600

Fax. (919) 361-1619

E-mail: info@excelight.com

URL: <http://www.excelight.com>

Europe

Sumitomo Electric Europe Ltd.

220 Centennial Park, Centennial Avenue, Elstree, Herts, WD6 3SL

United Kingdom

Tel. (020) 8953-8118

Fax. (020) 8207-5950

URL: <http://www.sumielectric.com>

Japan

Sumitomo Electric Industries, Ltd. (Opto-electronic Products Sales Div.)

3-12, Moto-Akasaka 1-chome, Minato-ku Tokyo, 107-8468

Japan

Tel. (03) 3423-5031

Fax. (03) 3423-5247

E-mail: product_info@ppd.sei.co.jp

URL: http://www.sei.co.jp/Electro-optic/index_e.html

Sumitomo Electric Industries, Ltd.
Part No.: SLT1330 Series
Document No.: HUW0224030-01A
Date of issue: June 21, 2002

Revision Record

Document No.	Date of issue	Description	Incorporated by	Checked by	Approved by
HUW0224030-01A	Jun./21/02	Preliminary issue.	T. Nakanishi	Y. Yamasaki	M. Yoshimura

Preliminary