

Microcontroller Pocket Guide

www.infineon.com/microcontrollers



32-bit microcontroller

Product type/part number	Markets			Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory			
	Automotive	Industrial	Consumer				Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock	SWD, SPD			JTAG, Trace	Flash	ECC	RAM
XMC1100 series																									
XMC1100-T016F0008	-	●	●	0.56	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	8	-	16
XMC1100-T016F0016	-	●	●	0.61	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1100-T016X0016	-	●	●	0.65	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1100-T016X0032	-	●	●	0.76	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1100-T016F0032	-	●	●	0.72	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1100-T016F0064	-	●	●	0.94	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1100-T016X0064	-	●	●	0.99	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1100-T038F0016	-	●	●	0.70	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1100-T038F0032	-	●	●	0.81	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1100-T038F0064	-	●	●	1.03	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1100-T038X0064	-	●	●	1.08	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1100-Q024F0008	-	●	●	0.61	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1100-Q024F0016	-	●	●	0.65	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1100-Q024F0032	-	●	●	0.76	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1100-Q024F0064	-	●	●	0.99	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1100-Q040F0016	-	●	●	0.72	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1100-Q040F0032	-	●	●	0.83	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1100-Q040F0064	-	●	●	1.06	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1200 series																									
XMC1200-T038F0200	-	●	●	1.91	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	200	-	16
XMC1201-T038F0016	-	●	●	0.79	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1201-T038F0032	-	●	●	0.89	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1201-T038F0064	-	●	●	1.12	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1201-T038F0128	-	●	●	1.46	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	128	-	16
XMC1201-T038F0200	-	●	●	1.91	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	200	-	16
XMC1201-Q040F0016	-	●	●	0.81	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog				Timer/PWM							Communication										LED display	Capacitive touch	
					No. of 12-bit ADC/ No. of sample & hold/ No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)									External Bus Unit (EBU)
																	# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/I ² C	IIS/I ² S	LIN				
-	•	-	•	64	1/1/7	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/7	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/7	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/7	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/7	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/7	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/12	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/12	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/12	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/12	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/9	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/9	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/9	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/9	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/12	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/12	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/1/12	-	-	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch

32-bit microcontroller

Product type/part number	Markets			Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory			
	Automotive	Industrial	Consumer				Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock	SWD, SPD			JTAG, Trace	Flash	ECC	RAM
XMC1200 series																									
XMC1201-Q040F0032	-	●	●	0.92	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1201-Q040F0064	-	●	●	1.15	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1201-Q040F0128	-	●	●	1.48	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	128	-	16
XMC1201-Q040F0200	-	●	●	1.93	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	200	-	16
XMC1201-T028F0016	-	●	●	0.74	TSSOP-28	26	Cortex®-M1	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1202-T016X0016	-	●	●	0.74	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1202-T016X0032	-	●	●	0.85	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1202-T028X0016	-	●	●	0.79	TSSOP-28	26	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1202-T028X0032	-	●	●	0.90	TSSOP-28	26	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1202-T028X0064	-	●	●	1.13	TSSOP-28	26	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1202-Q024X0016	-	●	●	0.79	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1202-Q024X0032	-	●	●	0.90	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1202-Q040X0016	-	●	●	0.85	VQFN-40	26	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1202-Q040X0032	-	●	●	0.97	VQFN-40	26	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1202-T016X0064	-	●	●	1.09	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 106	64	-	16
XMC1300 series																									
XMC1301-T016F0008	-	●	●	0.61	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	8	-	16
XMC1301-T016X0008	-	●	●	0.65	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	8	-	16
XMC1301-T016F0016	-	●	●	0.65	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1301-T016X0016	-	●	●	0.70	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1301-T038F0008	-	●	●	0.70	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	8	-	16
XMC1301-T038F0016	-	●	●	0.74	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1301-T038F0032	-	●	●	0.85	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1301-Q024F0008	-	●	●	0.65	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	8	-	16
XMC1301-Q024F0016	-	●	●	0.70	VQFN-24	22	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1301-Q040F0008	-	●	●	0.72	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	8	-	16

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog			Timer/PWM							Communication										LED display	Capacitive touch		
					No. of 12-bit ADC/ No. of sample & hold/ No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)								External Bus Unit (EBU)	
																	# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/I ² C	IIS/I ² S	LIN				
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/10	-	2x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	2x 64 segment	16 ch
-	•	-	•	64	1/2/7	-	2x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/10	-	3x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/10	-	3x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/10	-	3x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	-	-	-	-	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	-	-	-	-	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-

32-bit microcontroller

Product type/part number	Markets			Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory			
	Automotive	Industrial	Consumer				Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock	SWD, SPD			JTAG, Trace	Flash	ECC	RAM
XMC1300 series																									
XMC1301-Q040F0016	-	●	●	0.76	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1301-Q040F0032	-	●	●	0.88	VQFN-40	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1301-T016F0032	-	●	●	0.77	TSSOP-16	14	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1301-T038X0064	-	●	●	1.13	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1301-T038F0064	-	●	●	1.09	TSSOP-38	34	Cortex®-M0	32	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1302-T016X0008	-	●	●	0.70	TSSOP-16	14	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	8	-	16
XMC1302-T016X0016	-	●	●	0.74	TSSOP-16	14	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1302-T016X0032	-	●	●	0.85	TSSOP-16	14	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1302-T038X0016	-	●	●	0.83	TSSOP-38	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1302-T038X0032	-	●	●	0.94	TSSOP-38	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1302-T038X0064	-	●	●	1.17	TSSOP-38	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	8	-	16
XMC1302-T038X0128	-	●	●	1.51	TSSOP-38	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1302-T038X0200	-	●	●	1.96	TSSOP-38	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	200	-	16
XMC1302-Q024F0016	-	●	●	0.74	VQFN-24	22	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	16	-	16
XMC1302-Q024F0032	-	●	●	0.85	VQFN-24	22	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	32	-	16
XMC1302-Q024F0064	-	●	●	1.08	VQFN-24	22	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1302-Q024X0016	-	●	●	0.79	VQFN-24	22	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1302-Q024X0032	-	●	●	0.90	VQFN-24	22	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1302-Q024X0064	-	●	●	1.12	VQFN-24	22	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1302-Q040X0016	-	●	●	0.85	VQFN-40	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	16	-	16
XMC1302-Q040X0032	-	●	●	0.97	VQFN-40	26	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1302-Q040X0064	-	●	●	1.19	VQFN-40	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1302-Q040X0128	-	●	●	1.53	VQFN-40	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1302-Q040X0200	-	●	●	1.99	VQFN-40	34	Cortex®-M0	32	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	200	-	16

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog			Timer/PWM						Communication										LED display	Capacitive touch			
					No. of 12-bit ADC/ No. of sample & hold/ No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)							External Bus Unit (EBU)		
																	# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/I ² C	IIS/I ² S	LIN				
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	-	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	-	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	-	4 ch	-	-	1x	-	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/7	-	2x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/9	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-
-	•	-	•	64	1/2/12	-	3x	4 ch	4 ch	-	-	1x	9 ch	-	-	-	2 ch	•	•	•	•	•	•	•	•	-	-	-

32-bit microcontroller

Product type/part number	Markets			Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory			
	Automotive	Industrial	Consumer				Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock	SWD, SPD			JTAG, Trace	Flash	ECC	RAM
XMC1400 series																									
XMC1401-Q048F0064	-	●	●	1.27	VQFN-48	42	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	128	-	16
XMC1401-Q048F0128	-	●	●	1.63	VQFN-48	42	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	128	-	16
XMC1401-F064F0064	-	●	●	1.37	LQFP-64	55	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	64	-	16
XMC1401-F064F0128	-	●	●	1.72	LQFP-64	55	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 85	128	-	16
XMC1402-T038X0032	-	●	●	1.08	TSSOP-38	34	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1402-T038X0064	-	●	●	1.31	TSSOP-38	34	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1402-T038X0128	-	●	●	1.66	TSSOP-38	34	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1402-T038X0200	-	●	●	2.12	TSSOP-38	34	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	200	-	16
XMC1402-Q040X0032	-	●	●	1.08	VQFN-40	35	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1402-Q040X0064	-	●	●	1.31	VQFN-40	35	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1402-Q040X0128	-	●	●	1.67	VQFN-40	35	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1402-Q048X0032	-	●	●	1.12	VQFN-48	42	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	32	-	16
XMC1402-Q048X0064	-	●	●	1.36	VQFN-48	42	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1402-Q048X0128	-	●	●	1.72	VQFN-48	42	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1402-Q064X0064	-	●	●	1.46	VQFN-64	55	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1402-Q064X0128	-	●	●	1.82	VQFN-64	55	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1402-Q064X0200	-	●	●	2.29	VQFN-64	55	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	200	-	16
XMC1402-F064X0064	-	●	●	1.46	LQFP-64	55	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1402-F064X0128	-	●	●	1.82	LQFP-64	55	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1402-F064X0200	-	●	●	2.29	LQFP-64	55	Cortex®-M0	48	●	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	200	-	16
XMC1403-Q048X0064	-	●	●	1.39	VQFN-48	42	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1403-Q048X0128	-	●	●	1.74	VQFN-48	42	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1403-Q048X0200	-	●	●	2.22	VQFN-48	42	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	200	-	16
XMC1403-Q064X0064	-	●	●	1.48	VQFN-64	55	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1403-Q064X0128	-	●	●	1.84	VQFN-64	55	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1403-Q064X0200	-	●	●	2.32	VQFN-64	55	Cortex®-M0	48	-	-	-	1	-	-	-	●	●	●	●	-	1.8 to 5.5	-40 to 105	200	-	16

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog				Timer/PWM							Communication										LED display	Capacitive touch
					No. of 12-bit ADC/ No. of sample & hold/ No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)								
																	# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/ I ² C	IIS/ I ² S	LIN			
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	3x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	3x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	3x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	3x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	3x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	2	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	2	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	2	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	2	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	2	-	4 ch	•	•	•	•	•	•	•	-	-	-
-	•	-	•	96	1/2/12	-	-	8 ch	-	-	-	-	-	-	2	-	4 ch	•	•	•	•	•	•	•	-	-	-

32-bit microcontroller

Product type/part number	Markets			Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory			
	Automotive	Industrial	Consumer				Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock	SWD, SPD			JTAG, Trace	Flash	ECC	RAM
XMC1400 series																									
XMC1404-Q048X0064	-	•	•	1.48	VQFN-48	42	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1404-Q048X0128	-	•	•	1.84	VQFN-48	42	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1404-Q048X0200	-	•	•	2.32	VQFN-48	42	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	200	-	16
XMC1404-Q064X0064	-	•	•	1.58	VQFN-64	55	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1404-Q064X0128	-	•	•	1.94	VQFN-64	55	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1404-Q064X0200	-	•	•	2.41	VQFN-64	55	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	200	-	16
XMC1404-F064X0064	-	•	•	1.58	LQFP-64	55	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	64	-	16
XMC1404-F064X0128	-	•	•	1.94	LQFP-64	55	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	128	-	16
XMC1404-F064X0200	-	•	•	2.41	LQFP-64	55	Cortex®-M0	48	•	-	-	1	-	-	-	•	•	•	•	-	1.8 to 5.5	-40 to 105	200	-	16
XMC4100 series																									
XMC4108-Q48K64	-	•	•	2.17	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	64	•	20
XMC4108-F64K64	-	•	•	2.52	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	64	•	20
XMC4104-Q48F64	-	•	•	2.70	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 85	64	•	20
XMC4104-Q48F128	-	•	•	2.80	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 85	128	•	20
XMC4104-Q48K64	-	•	•	2.97	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	64	•	20
XMC4104-Q48K128	-	•	•	3.09	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	128	•	20
XMC4104-F64F64	-	•	•	2.82	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 85	64	•	20
XMC4104-F64F128	-	•	•	2.92	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 85	128	•	20
XMC4104-F64K64	-	•	•	3.20	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	64	•	20
XMC4104-F64K128	-	•	•	3.31	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	128	•	20
XMC4100-Q48F128	-	•	•	3.01	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 85	128	•	20
XMC4100-Q48K128	-	•	•	3.21	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	128	•	20
XMC4100-F64F128	-	•	•	3.12	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 85	128	•	20
XMC4100-F64K128	-	•	•	3.54	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	3.13 to 3.63	-40 to 125	128	•	20

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog				Timer/PWM						Communication										LED display	Capacitive touch			
					No. of 12-bit ADC/ No. of sample & hold/ No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)								External Bus Unit (EBU)		
																		# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/°C	IIS/°S	LIN				
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
-	•	-	•	96	1/2/12	-	4x	8 ch	8 ch	-	-	2x	9 ch	-	-	2	-	-	4 ch	•	•	•	•	•	•	•	-	3x 64 segment	24 ch
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	-	-	1x	-	-	-	1	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	-	-	1x	-	-	-	1	-	-	4 ch	•	•	•	•	•	•	•	-	-	-
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	-	-	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch

32-bit microcontroller

Product type/part number	Markets			Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory				
	Automotive	Industrial	Consumer				Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock	SWD, SPD			JTAG, Trace	Flash	ECC	RAM	
XMC4200 series																										
XMC4200-Q48F256	-	•	•	3.12	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	256	•	40
XMC4200-Q48K256	-	•	•	3.33	VQFN-48	30	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	256	•	40
XMC4200-F64F256	-	•	•	3.22	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	256	•	40
XMC4200-F64K256	-	•	•	3.66	TQFP-64	45	Cortex®-M4	80	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	256	•	40
XMC4300 series																										
XMC4300-F100F256	-	•	-	7.97	LQFP-100	75	Cortex®-M4	144	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	256	•	128
XMC4300-F100K256	-	•	-	8.77	LQFP-100	75	Cortex®-M4	144	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	256	•	128
XMC4400 series																										
XMC4402-F64F256	-	•	•	4.23	TQFP-64	41	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	256	•	80
XMC4402-F64K256	-	•	•	4.80	TQFP-64	41	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	256	•	80
XMC4402-F100F256	-	•	•	4.53	LQFP-100	75	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	256	•	80
XMC4402-F100K256	-	•	•	5.14	LQFP-100	75	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	256	•	80
XMC4400-F64F256	-	•	•	4.43	TQFP-64	41	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	256	•	80
XMC4400-F64F512	-	•	•	4.64	TQFP-64	41	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	512	•	80
XMC4400-F64K256	-	•	•	5.03	TQFP-64	41	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	256	•	80
XMC4400-F64K512	-	•	•	5.26	TQFP-64	41	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	512	•	80
XMC4400-F100F256	-	•	•	4.88	LQFP-100	75	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	256	•	80
XMC4400-F100F512	-	•	•	4.94	LQFP-100	75	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	512	•	80
XMC4400-F100K256	-	•	•	5.37	LQFP-100	75	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	256	•	80
XMC4400-F100K512	-	•	•	5.43	LQFP-100	75	Cortex®-M4	120	-	•	•	2	8 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	512	•	80

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog			Timer/PWM							Communication										LED display	Capacitive touch				
					No. of 12-bit ADC/ No. of sample & hold/ No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)								External Bus Unit (EBU)			
																		# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/™C	IIS/™S	LIN					
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/8	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
1	•	•	-	80	2/2/9	2 ch	-	8 ch	4 ch	•	-	1x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
8	•	•	-	144	2/2/14	2 ch	-	8 ch	4 ch	-	-	-	-	-	•	•	2	•	•	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
8	•	•	-	144	2/2/14	2 ch	-	8 ch	4 ch	-	-	-	-	-	•	•	2	•	•	4 ch	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/9	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/9	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/18	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/18	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	-	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/9	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	•	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/9	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	•	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/9	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	•	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/18	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	•	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/18	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	•	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/18	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	•	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch
4	•	•	-	120	4/4/18	2 ch	-	16 ch	8 ch	•	4 ch	2x	-	-	•	2	•	-	4 ch	•	•	•	•	•	•	•	•	-	1x 64 segment	8 ch

32-bit microcontroller

Product type/part number	Markets		Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory					
	Automotive	Industrial				Consumer	Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock			SWD, SPD	JTAG, Trace	Flash	ECC	RAM	
XMC4500 series																										
XMC4504-F100F512	-	•	•	4.79	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	512	•	128
XMC4504-F100K512	-	•	•	5.27	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	512	•	128
XMC4504-F144F512	-	•	•	5.18	LQFP-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	512	•	128
XMC4504-F144K512	-	•	•	5.70	LQFP-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	512	•	128
XMC4502-F100F768	-	•	•	5.18	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	768	•	160
XMC4502-F100K768	-	•	•	5.70	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	768	•	160
XMC4500-F100F768	-	•	•	5.57	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	768	•	160
XMC4500-F100F1024	-	•	•	5.77	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1024	•	160
XMC4500-F100K768	-	•	•	6.13	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	768	•	160
XMC4500-F100K1024	-	•	•	6.54	LQFP-100	75	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1024	•	160
XMC4500-F144F768	-	•	•	5.96	LQFP-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	768	•	160
XMC4500-F144F1024	-	•	•	6.16	LQFP-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1024	•	160
XMC4500-F144K768	-	•	•	6.13	LQFP-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	768	•	160
XMC4500-F144K1024	-	•	•	6.77	LQFP-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1024	•	160
XMC4500-E144F1024	-	•	•	6.67	LFBGA-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1024	•	160
XMC4500-E144X1024	-	•	•	7.08	LFBGA-144	119	Cortex®-M4	120	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 105	1024	•	160
XMC4700 series																										
XMC4700-F100F1536	-	•	•	7.16	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1536	•	276
XMC4700-F100F2048	-	•	•	7.97	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	2048	•	352
XMC4700-F100K1536	-	•	•	7.88	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1536	•	276
XMC4700-F100K2048	-	•	•	8.77	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	2048	•	352
XMC4700-F144F1536	-	•	•	7.58	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1536	•	276
XMC4700-F144F2048	-	•	•	8.38	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	2048	•	352
XMC4700-F144K1536	-	•	•	8.34	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	40 to 125	1536	•	276
XMC4700-F144K2048	-	•	•	9.22	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	2048	•	352

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog			Timer/PWM						Communication										LED display	Capacitive touch				
					No. of 12-bit ADC/ No. of sample & hold/ No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)							External Bus Unit (EBU)			
																# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/IC	IIS/I ² S	LIN						
4	●	●	-	120	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	-	-	●	6 ch	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	-	-	●	6 ch	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	-	-	●	6 ch	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	-	-	●	6 ch	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	-	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	-	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
4	●	●	-	120	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	3	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch
8	●	●	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	●	6	●	●	●	●	●	●	●	●	●	●	●	1x 64 segment	8 ch

32-bit microcontroller

Product type/part number	Markets			Budgetary web price [€/1 kpcs]	Package	GPIOs	Core		Co-processor			System						Debug		Supply voltage [V]	Operating temperature range T _A [°C]	Memory				
	Automotive	Industrial	Consumer				Processor type	Core frequency [MHz]	CORDIC/DIV	DSP	FPU	ERU	DMA	MPU	CRC	PRNG	Watchdog	Real-Time Clock	SWD, SPD			JTAG, Trace	Flash	ECC	RAM	
XMC4700 series																										
XMC4700-E196F1536	-	•	•	7.99	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1536	•	276
XMC4700-E196F2048	-	•	•	8.80	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	2048	•	352
XMC4700-E196K1536	-	•	•	8.79	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1536	•	276
XMC4700-E196K2048	-	•	•	9.68	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	2048	•	352
XMC4800 series																										
XMC4800-F100F1024	-	•	-	11.84	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1024	•	200
XMC4800-F100F1536	-	•	-	12.71	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1536	•	276
XMC4800-F100F2048	-	•	-	13.58	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	2048	•	352
XMC4800-F100K1024	-	•	-	13.02	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1024	•	200
XMC4800-F100K1536	-	•	-	13.98	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1536	•	276
XMC4800-F100K2048	-	•	-	14.94	LQFP-100	75	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	2048	•	352
XMC4800-F144F1024	-	•	-	12.29	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1024	•	200
XMC4800-F144F1536	-	•	-	13.16	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1536	•	276
XMC4800-F144F2048	-	•	-	14.03	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	2048	•	352
XMC4800-F144K1024	-	•	-	13.51	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1024	•	200
XMC4800-F144K1536	-	•	-	14.47	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1536	•	276
XMC4800-F144K2048	-	•	-	15.43	LQFP-144	119	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	2048	•	352
XMC4800-E196F1024	-	•	-	12.73	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1024	•	200
XMC4800-E196F1536	-	•	-	13.60	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	1536	•	276
XMC4800-E196F2048	-	•	-	14.47	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 85	2048	•	352
XMC4800-E196K1024	-	•	-	14.01	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1024	•	200
XMC4800-E196K1536	-	•	-	14.96	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	1536	•	276
XMC4800-E196K2048	-	•	-	15.92	LFBGA-196	155	Cortex®-M4	144	-	•	•	2	12 ch	1	1	•	•	•	•	•	•	3.13 to 3.63	-40 to 125	2048	•	352

BCCU = Brightness and Color Control Unit for LED lighting

CCU = Capture Compare Unit

FPU = Floating Point Unit

MMC = Multi Media Card

POSIF = Motor Position Interface

SDIO = SD Card Interface with Input/Output

USIC = UART/SCI, SPI, Dual-SPI, Quad-SPI, IIC/I²C, IIS/I²S, LIN

Cache	EEPROM emulation in flash	Data/IP protection	Secure bootloader	Peripherals clock [MHz]	Analog			Timer/PWM						Communication											LED display	Capacitive touch																				
					No. of 12-bit ADC/No. of sample & hold/No. of inputs	12-bit DAC	Comparator	CCU4	CCU8	HRPWM (150 ps)	$\Delta\Sigma$ Demodulator	POSIF	BCCU/LED	EtherCAT®	IEEE1588 Ethernet MAC	CAN 2.0B nodes	USB	SDIO/SD/MMC	USIC (Universal Serial Interface Controller)								External Bus Unit (EBU)																			
																		# channels	SPI	Dual SPI	Quad SPI	UART/SCI	IIC/C	IIS/I ² S	LIN																					
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch												
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch											
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch										
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	-	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch									
8	•	•	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch									
8	•	•	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch								
8	•	•	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch							
8	•	•	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch						
8	•	•	-	144	4/4/18	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch					
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch				
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch			
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch		
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch		
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch		
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch	
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch
8	•	•	-	144	4/4/26	2 ch	-	16 ch	8 ch	-	4 ch	2x	-	•	•	6	•	•	6 ch	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1x 64 segment	8 ch

32-bit microcontroller

Product type	Markets			Package Package (Pitch)	TriCore™		Program flash			Data flash			SRAM Total (DMI, PMI) [KB]	DMA Channels	ADC		Timer - GTM		
	Automotive	Industrial	Consumer		Temperature T _A [°C]	# Cores/checker	Max frequency [MHz]	Size [MB]	Data retention	Physical size [kb]	Erase cycles	Data retention			Channels	Modules 12-bit (SAR) / 16-bit (DS)	Channels VADC/DSADC	GTM input/output channels	TOM – standard 16-bit PWM ch.
AURIX™ – family																			
SAK-TC299TX-128F300	●	●	–	125	LFBGA-516 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	2776	128	11/10	84/10 diff	48/152	80	72
SAK-TC299TY-128F300	●	●	–	125	LFBGA-516 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	2776	128	11/10	84/10 diff	48/152	80	72
SAK-TC299TP-128F300	●	●	–	125, 150	LFBGA-516 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	728	128	11/10	84/10 diff	48/152	80	72
SAK-TC298TP-128F300	●	●	–	125, 150	LFBGA-416 (1.0 mm)	3/1	300	8	20 years	768	125 k	10 years	728	128	11/10	62/10 diff	48/152	80	72
SAK-TC297TA-128F300	●	●	–	125	LFBGA-292 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	2776	128	11/10	60/6 diff	48/152	80	72
SAK-TC297TB-128F300	●	●	–	125	LFBGA-292 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	2776	128	11/10	60/6 diff	48/152	80	72
SAK-TC297TX-128F300	●	●	–	125	LFBGA-292 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	2776	128	11/10	60/6 diff	48/152	80	72
SAK-TC297TY-128F300	●	●	–	125	LFBGA-292 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	2776	128	11/10	60/6 diff	48/152	80	72
SAK-TC297TP-128F300	●	●	–	125, 150	LFBGA-292 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	728	128	11/10	60/6 diff	48/152	80	72
SAK-TC297T-128F300	●	●	–	125, 150	LFBGA-292 (0.8 mm)	3/1	300	8	20 years	768	125 k	10 years	728	128	11/10	60/6 diff	48/152	80	72
SAK-TC277TP-64F200	●	●	–	125, 150	LFBGA-292 (0.8 mm)	3/2	200	4	20 years	384	125 k	10 years	472	64	8/6	60/6 diff	32/88	48	40
SAK-TC277T-64F200	●	●	–	125, 150	LFBGA-292 (0.8 mm)	3/2	200	4	20 years	384	125 k	10 years	472	64	8/6	60/6 diff	32/88	48	40
SAK-TC275TP-64F200	●	●	–	125, 150	LQFP-176 (0.5 mm)	3/2	200	4	20 years	384	125 k	10 years	472	64	8/6	48/6 diff	32/88	48	40
SAK-TC275T-64F200	●	●	–	125, 150	LQFP-176 (0.5 mm)	3/2	200	4	20 years	384	125 k	10 years	472	64	8/6	48/6 diff	32/88	48	40
SAK-TC267D-40F200	●	●	–	125, 150	LFBGA-292 (0.8 mm)	2/1	200	2.5	20 years	96	125 k	10 years	240	48	4/3	56/3 diff	24/ 64	32	32
SAK-TC265D-40F200	●	●	–	125, 150	LQFP-176 (0.5 mm)	2/1	200	2.5	20 years	96	125 k	10 years	240	48	4/3	50/3 diff	24/ 64	32	32
SAK-TC264DA-40F200	●	●	–	125	LQFP-144 (0.5 mm)	2/1	200	2.5	20 years	96	125 k	10 years	752	48	4/3	40/3 diff	24/ 64	32	32
SAK-TC264D-40F200	●	●	–	125, 150	LQFP-144 (0.5 mm)	2/1	200	2.5	20 years	96	125 k	10 years	240	48	4/3	40/3 diff	24/ 64	32	32

DTM – 2x, 4 ch	Timer	Interfaces															Safety	Security	Power	
		CCU/GPT modules	FlexRay (#/ch.)	CAN-FD (nodes/obj)(DIS 2014)	CAN-FD (nodes/obj)(DIS 2015)	Queued Synchronous Peripheral Interface (QSPI)	Asynchronous/Synchronous Interface (ASCLIN)	Inter-Integrated Circuit Bus Interface (I ² C)	Single Edge Nibble Transmission (SENT)	Peripheral Sensor Interface (PSI5)	PSI with Serial PHY Connection (PSI5S)	High-Speed Communication Tunnel (HSCT)	Micro Second Channel (MSC)	External bus interface e.g. ext. memory	FFT accelerator engine	Camera (incl. pixel preprocessing) & ext. ADC 16-bit interface (CIF)			Ethernet MAC 100 Mbit/s	SIL level
-	2/1	2/4	6/384	4	6	4	2	15	5	1	1	3 diff LVDS	1	-	-	1	ASIL-D	Yes	Yes	SRAM
-	2/1	2/4	6/384	4	6	4	2	15	5	1	1	3 diff LVDS	1	-	-	1	ASIL-D	No	Yes	SRAM
-	2/1	2/4	6/384	4	6	4	2	15	5	1	1	3 diff LVDS	1	-	-	1	ASIL-D	Yes	Yes	SRAM
-	2/1	2/4	6/384	4	4	4	2	15	5	1	1	3 diff LVDS	1	-	-	1	ASIL-D	Yes	Yes	SRAM
-	2/1	2/4	6/384	4	5	4	2	15	5	1	1	3 diff LVDS	-	1	1	1	ASIL-D	Yes	Yes	SRAM
-	2/1	2/4	6/384	4	5	4	2	15	5	1	1	3 diff LVDS	-	1	1	1	ASIL-D	No	Yes	SRAM
-	2/1	2/4	6/384	4	5	4	2	15	5	1	1	3 diff LVDS	-	-	-	1	ASIL-D	Yes	Yes	SRAM
-	2/1	2/4	6/384	4	5	4	2	15	5	1	1	3 diff LVDS	-	-	-	1	ASIL-D	Yes	Yes	SRAM
-	2/1	2/4	6/384	4	5	4	2	15	5	1	1	3 diff LVDS	-	-	-	1	ASIL-D	No	Yes	SRAM
-	2/1	1/2	4/256	4	4	4	1	10	3	1	1	2 diff LVDS	-	-	-	1	ASIL-D	Yes	Yes	SRAM
-	2/1	1/2	4/256	4	4	4	1	10	3	1	1	2 diff LVDS	-	-	-	1	ASIL-D	No	Yes	SRAM
-	2/1	1/2	4/256	4	4	4	1	10	3	1	1	2 diff LVDS	-	-	-	1	ASIL-D	Yes	Yes	SRAM
-	2/1	1/2	4/256	4	4	4	1	10	3	1	1	2 diff LVDS	-	-	-	1	ASIL-D	No	Yes	SRAM
-	2/1	1/2	5/256	No	4	4	1	6	2	1	1	2 diff LVDS	-	-	-	1	ASIL-D	No	Yes	Yes
-	2/1	1/2	5/256	4	4	4	1	6	2	1	1	2 diff LVDS	-	-	-	1	ASIL-D	No	Yes	Yes
-	2/1	1/2	5/256	4	4	4	1	6	2	1	1	2 diff LVDS	-	1	1	1	ASIL-D	No	Yes	Yes
-	2/1	1/2	5/256	4	4	4	1	6	2	1	1	2 diff LVDS	-	-	-	1	ASIL-D	No	Yes	Yes

32-bit microcontroller

Product type	Markets			Temperature T_A [°C]	Package (Pitch)	TriCore™		Program flash		Data flash			SRAM	DMA	ADC		Timer - GTM		
	Automotive	Industrial	Consumer			# Cores/checker	Max frequency [MHz]	Size [MB]	Data retention	Physical size [kb]	Erase cycles	Data retention			Total (DMI, PMI) [KB]	Channels	Modules 12-bit (SAR) / 16-bit (DS)	Channels VADC/DSADC	GTM input/output channels
AURIX™ – family																			
SAK-TC234LA-32F200	●	●	-	125	TQFP-144 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	704	16	4/-	24/-	8/32	32	-
SAK-TC234LX-32F200	●	●	-	125	TQFP-144 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	704	16	2/-	24/-	8/32	32	-
SAK-TC237LP-32F200	●	●	-	125, 150	LFBGA-292 (0.8 mm)	1/1	200	2	20 years	128	125 k	10 years	192	16	2/-	24/-	8/32	32	-
SAK-TC234LP-32F200	●	●	-	125, 150	TQFP-144 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	192	16	2/-	24/-	8/32	32	-
SAK-TC234L-32F200	●	●	-	125, 150	TQFP-144 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	192	16	2/-	24/-	8/32	32	-
SAK-TC233L-32F200	●	●	-	125, 150	TQFP-100 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	192	16	2/-	24/-	8/32	32	-
SAK-TC233LP-32F200	●	●	-	125, 150	TQFP-100 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	192	16	2/-	24/-	8/32	32	-
SAK-TC224L-16F133	●	●	-	125, 150	TQFP-144 (0.4 mm)	1/1	133	1	20 years	96	125 k	10 years	96	16	2/-	24/-	8/32	32	-
SAK-TC224S-16F133	●	●	-	125, 150	TQFP-144 (0.4 mm)	1/0	133	1	20 years	96	125 k	10 years	96	16	2/-	24/-	8/32	32	-
SAK-TC223L-16F133	●	●	-	125, 150	TQFP-100 (0.4 mm)	1/1	133	1	20 years	96	125 k	10 years	96	16	2/-	24/-	8/32	32	-
SAK-TC223S-16F133	●	●	-	125, 150	TQFP-100 (0.4 mm)	1/0	133	1	20 years	96	125 k	10 years	96	16	2/-	24/-	8/32	32	-
SAK-TC222L-16F133	●	●	-	125, 150	TQFP-80 (0.4 mm)	1/1	133	1	20 years	96	125 k	10 years	96	16	2/-	24/-	8/32	32	-
SAK-TC222S-16F133	●	●	-	125, 150	TQFP-80 (0.4 mm)	1/0	133	1	20 years	96	125 k	10 years	96	16	2/-	24/-	8/32	32	-
SAK-TC214L-8F133	●	●	-	125, 150	TQFP-144 (0.4 mm)	1/1	133	0.5	20 years	64	125 k	10 years	56	16	2/-	24/-	8/32	32	-
SAK-TC214S-8F133	●	●	-	125, 150	TQFP-144 (0.4 mm)	1/0	133	0.5	20 years	64	125 k	10 years	56	16	2/-	24/-	8/32	32	-
SAK-TC213L-8F133	●	●	-	125, 150	TQFP-100 (0.4 mm)	1/1	133	0.5	20 years	64	125 k	10 years	56	16	2/-	24/-	8/32	32	-
SAK-TC213S-8F133	●	●	-	125, 150	TQFP-100 (0.4 mm)	1/0	133	0.5	20 years	64	125 k	10 years	56	16	2/-	24/-	8/32	32	-
SAK-TC212L-8F133	●	●	-	125, 150	TQFP-80 (0.4 mm)	1/1	133	0.5	20 years	64	125 k	10 years	56	16	2/-	24/-	8/32	32	-
SAK-TC212S-8F133	●	●	-	125, 150	TQFP-80 (0.4 mm)	1/0	133	0.5	20 years	64	125 k	10 years	56	16	2/-	24/-	8/32	32	-

DTM - 2x, 4 ch	Timer	Interfaces														Safety	Security	Power		
		CCU/GPT modules	FlexRay (#/ch.)	CAN-FD (nodes/obj)(DIS 2014)	CAN-FD (nodes/obj)(DIS 2015)	Queued Synchronous Peripheral Interface (QSPI)	Asynchronous/Synchronous Interface (ASCLIN)	Inter-Integrated Circuit Bus Interface (I2C)	Single Edge Nibble Transmission (SENT)	Peripheral Sensor Interface (PSI5)	PSI with Serial PHY Connection (PSI5S)	High-Speed Communication Tunnel (HSCT)	Micro Second Channel (MSC)	External bus interface e.g. ext. memory	FFT accelerator engine			Camera (incl. pixel preprocessing) & ext. ADC 16-bit interface (CIF)	Ethernet MAC 100 Mbit/s	SIL level
2	2/1	1/2	6/256	No	4	2	-	4	-	-	-	-	-	1	-	1	ASIL-D	Yes	Yes	WUT + SRAM
2	2/1	1/2	6/256	No	4	2	-	4	-	-	-	-	-	-	-	1	ASIL-D	Yes	Yes	WUT + SRAM
2	2/1	1/2	6/256	4	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	Yes	Yes	WUT + SRAM
2	2/1	1/2	6/256	4	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	Yes	Yes	WUT + SRAM
2	2/1	1/2	6/256	4	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	No	Yes	WUT + SRAM
2	2/1	1/2	6/256	4	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	No	Yes	WUT + SRAM
2	2/1	1/2	6/256	4	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	Yes	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	No	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-B	No	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	No	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-B	No	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	No	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-B	No	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-D	No	Yes	WUT + SRAM
2	2/1	-	3/128	3	4	2	-	4	-	-	-	-	-	-	-	-	ASIL-B	No	Yes	WUT + SRAM

32-bit microcontroller

Product type	Markets			Temperature T _A [°C]	Package (Pitch)	TriCore™		Program flash		Data flash			SRAM Total (DMI, PMI) [KB]	DMA Channels
	Automotive	Industrial	Consumer			# Cores/checker	Max frequency [MHz]	Size [MB]	Data retention	Physical size [kb]	Erase cycles	Data retention		
AURIX™ – family														
TC397XA-256F300S	●	●	–	125	LFBGA-292 (0.8 mm)	6/4	300	16	20 years	512	125 k	10 years	6912	128
TC399XX-256F300S	●	●	–	125–150	LFBGA-516 (0.8 mm)	6/4	300	16	20 years	512	125 k	10 years	6912	128
TC399XP-256F300S	●	●	–	125–150	LFBGA-516 (0.8 mm)	6/4	300	16	20 years	512	125 k	10 years	2816	128
TC397XX-256F300S	●	●	–	125–150	LFBGA-292 (0.8 mm)	6/4	300	16	20 years	512	125 k	10 years	6912	128
TC397XP-256F300S	●	●	–	125–150	LFBGA-292 (0.8 mm)	6/4	300	16	20 years	512	125 k	10 years	2816	128
TC389QP-160F300S	●	●	–	125–150	LFBGA-516 (0.8 mm)	4/2	300	10	20 years	512	125 k	10 years	1568	128
TC387QP-160F300S	●	●	–	125–150	LFBGA-292 (0.8 mm)	4/2	300	10	20 years	512	125 k	10 years	1568	128
TC377TX-96F300S	●	●	–	125	LFBGA-292 (0.8 mm)	3/3	300	6	20 years	256	125 k	10 years	4208	128
TC377TP-96F300S	●	●	–	125–150	LFBGA-292 (0.8 mm)	3/2	300	6	20 years	256	125 k	10 years	1136	128
TC375TP-96F300W	●	●	–	125–150	LQFP-176 (0.5 mm)	3/2	300	6	20 years	256	125 k	10 years	1136	128
TC367DP-64F300S	●	●	–	125–150	LFBGA-292 (0.8 mm)	2/2	300	4	20 years	128	125 k	10 years	672	64
TC365DP-64F300W	●	●	–	125–150	LQFP-176 (0.5 mm)	2/2	300	4	20 years	128	125 k	10 years	672	64
TC364DP-64F300W	●	●	–	125–150	LQFP-176 (0.5 mm)	2/2	300	4	20 years	128	125 k	10 years	672	64
TC364DP-64F300F	●	●	–	125–150	TQFP-144 (0.4 mm)	2/2	300	4	20 years	128	125 k	10 years	672	64
TC357TA-64F300S	●	●	–	125	LFBGA-292 (0.8 mm)	3/2	300	4	20 years	128	125 k	10 years	3152	64
TC337DA-32F200S	●	●	–	125	LFBGA-292 (0.8 mm)	2/1	200	2	20 years	128	125 k	10 years	1328	16
TC337LP-32F200S	●	●	–	125–150	LFBGA-292 (0.8 mm)	1/1	200	2	20 years	128	125 k	10 years	248	16
TC334LP-32F200F	●	●	–	125–150	TQFP-144 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	248	16
TC333LP-32F200F	●	●	–	125–150	TQFP-100 (0.4 mm)	1/1	200	2	20 years	128	125 k	10 years	248	16
TC327LP-16F160S	●	●	–	125–150	LFBGA-292 (0.8 mm)	1/1	160	1	20 years	96	125 k	10 years	152	16
TC324LP-16F160F	●	●	–	125–150	TQFP-144 (0.4 mm)	1/1	160	1	20 years	96	125 k	10 years	152	16
TC323LP-16F160F	●	●	–	125–150	TQFP-100 (0.4 mm)	1/1	160	1	20 years	96	125 k	10 years	152	16

ASC = Asynchronous Serial Channel
EVR = Embedded Voltage Regulator

FPU = Floating Point Unit
MSC = Micro Second Channel

MLI = Micro Link Interface
PCP = Peripheral Control Processor

Timer	Interfaces														Safety	Security	Power	
GTM/CCU/GPT modules	FlexRay (#/ch.)	CAN-FD	Queued Synchronous Peripheral Interface (QSPI)	Asynchronous/Synchronous Interface (ASCLIN)	Inter-Integrated Circuit Bus Interface (I ² C)	Single Edge Nibble Transmission (SENT)	Peripheral Sensor Interface (PSIS)	PSI with Serial PHY Connection (PSI5S)	High-Speed Communication Tunnel (HSCT)	Micro Second Channel (MSC)	External bus interface e.g. ext. memory	Signal Processing Unit (SPU)	Camera (incl. pixel preprocessing) & ext. ADC 16-bit interface (CIF)	Ethernet MAC 100 Mbit/s	SIL level	Hardware Security Module (HSM)	Embedded Voltage Regulator (EVR) (5V/3.3V)	Standby control unit
Yes/Yes/Yes	4	12	6	12	2	17	4	Yes	2	2	-	2	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	4	12	6	12	2	25	4	Yes	2	4	yes	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	4	12	6	12	2	25	4	Yes	2	4	yes	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	4	12	6	12	2	20	4	Yes	2	2	-	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	4	12	6	12	2	20	4	Yes	2	2	-	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	4	12	5	24	2	25	4	Yes	1	3	-	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	4	12	5	24	2	20	4	Yes	1	2	-	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	12	5	12	1	15	2	Yes	1	2	-	-	1	2/2	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	5	12	1	15	2	Yes	1	2	-	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	5	12	1	15	2	Yes	1	2	-	-	-	1/0	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	12	1	10	2	Yes	1	1	-	-	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	12	1	10	2	Yes	1	1	-	-	-	1/0	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	12	1	10	2	Yes	1	1	-	-	-	1/0	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	11	1	10	2	Yes	1	1	-	-	-	1/0	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	4	-	-	-	-	-	-	-	2	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	12	-	6	-	-	-	-	-	1	-	1/1	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	12	-	6	-	-	-	-	-	-	-	-/-	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	11	-	6	-	-	-	-	-	-	-	-/-	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	6	4	12	-	6	-	-	-	-	-	-	-	-/-	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	4	-	6	-	-	-	-	-	-	-	-/-	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	8	4	4	-	6	-	-	-	-	-	-	-	-/-	ASIL-D	Full eVita	Yes	Yes (8 bit)
Yes/Yes/Yes	2	6	4	4	-	6	-	-	-	-	-	-	-	-/-	ASIL-D	Full eVita	Yes	Yes (8 bit)

SDIO = SD Card Interface with Input/Output
SENT = Single Edge Nibble Transmission

SSC = Synchronous Serial Channel
USIC = ASC, SPI, I²C, I²S

K = -40/+125 °C

16/32-bit microcontroller

Product type	Automotive	Industrial	Consumer	Temperature ranges	Package	Max clock frequency [MHz]	Program memory [kByte]	SRAM (incl. cache) [kByte]	Co-processor
XC2000 family – for automotive applications									
XC2200 for body applications									
U-series									
XC2220U	●	–	–	F, K	VQFN-48	40	32–64	8	MAC
L-series									
XC2224L	●	–	–	F, K	VQFN-48	66	96–160	12	MAC
XC2234L	●	–	–	F, K	LQFP-64	66	96–160	12	MAC
N-series									
XC2238N	●	–	–	F, K	LQFP-64	80	192–320	34	MAC
XC2268N	●	–	–	F, K	LQFP-100	80	192–320	34	MAC
M-series									
XC2237M	●	–	–	F, K	LQFP-64	80	448–832	50	MAC
XC2267M	●	–	–	F, K	LQFP-100	80	448–832	50	MAC
XC2287M	●	–	–	F, K	LQFP-144	80	448–832	50	MAC
I-series									
XC2269I	●	–	–	F, K	LQFP-100	128	1088	90	MAC
XC2289I	●	–	–	F, K	LQFP-144	128	1088	90	MAC
H-series									
XC2289H	●	–	–	F, K	LQFP-144	100	1600	138	MAC
XC2299H	●	–	–	F, K	LQFP-176	100	1600	138	MAC
XC2300 for safety applications									
A-series									
XC2336A	●	–	–	F, K	LQFP-64	40	448–832	50	MAC
XC2365A	●	–	–	F, K	LQFP-100	80	448–832	50	MAC
XC2387A	●	–	–	F, K	LQFP-144	80	448–832	50	MAC
B-series									
XC2336B	●	–	–	F, K	LQFP-64	80	320	34	MAC
XC2365B	●	–	–	F, K	LQFP-100	80	192–320	18–34	MAC
C-series									
XC2388C	●	–	–	F, K	LQFP-144	100	1088–1600	138	MAC

Digital I/O lines	Number of ADC channels	Timed IO channels (PWM, capture)	External bus interface	CAN nodes	Ethernet	Communication interfaces	Additional features / remarks
33	10	17	✓	–	–	1x USIC	–
33	10	23	✓	2	–	2x USIC	–
49	19	24	✓	2	–	2x USIC	CuWb
38	9	22	✓	6	–	4x USIC	CuWb
76	16	32	✓	6	–	6x USIC	CuWb
38	9	22	✓	6	–	6x USIC	–
76	16	32	✓	6	–	8x USIC	CuWb
119	24	44	✓	6	–	8x USIC	CuWb
76	19	32	✓	6	–	10x USIC, 2x FlexRay	CuWb
118	28	44	✓	6	–	10x USIC, 2x FlexRay	CuWb
119	24	44	✓	4	–	10x USIC, 2x FlexRay	–
150	30	66	✓	6	–	10x USIC, 2x FlexRay	–
38	9	24	✓	2	–	4x USIC	–
76	16	24	✓	3	–	6x USIC	CuWb
119	24	32	✓	3	–	6x USIC	CuWb
38	9	20	✓	2	–	4x USIC	CuWb
76	16	24	✓	3	–	6x USIC	CuWb
119	24	32	✓	4	–	10x USIC, 2x FlexRay	–

16/32-bit microcontroller

Product type	Automotive	Industrial	Consumer	Temperature ranges	Package	Max clock frequency [MHz]	Program memory [kByte]	SRAM (incl. cache) [kByte]	Co-processor
XC2300 for safety applications									
D-series									
XC2321D	●	-	-	F, K	VQFN-48	80	96-160	12	MAC
XC2331D	●	-	-	F, K	LQFP-64	80	96-160	12	MAC
E-series									
XC2368E	●	-	-	F, K	LQFP-100	128	576-1088	90	MAC
XC2388E	●	-	-	F, K	LQFP-144	128	576-1088	90	MAC
S-series									
XC2320S	●	-	-	F, K	VQFN-48	66	32-64	8	MAC
XC2700 for powertrain applications									
2-series									
XC2722X	●	-	-	K	VQFN-48	40	64	8	MAC
3-Series									
XC2723X	●	-	-	K	VQFN-48	66	160	12	MAC
XC2733X	●	-	-	K	LQFP-64	66	160	12	MAC
4-series									
XC2734X	●	-	-	K	LQFP-64	80	320	34	MAC
XC2764X	●	-	-	K	LQFP-100	80	320	34	MAC
5-series									
XC2765X	●	-	-	K	LQFP-100	80	576-832	50	MAC
XC2785X	●	-	-	K	LQFP-144	80	576-832	50	MAC
7-series									
XC2787X	●	-	-	K	LQFP-144	100	1600	138	MAC
8-series									
XC2768X	●	-	-	K	LQFP-100	128	1088	90	MAC
XC2788X	●	-	-	K	LQFP-144	128	1088	90	MAC

MAC = Multiply-Accumulate-Unit (DSP)

USIC = ASC, SPI, I²C, I²S

F = -40/+85 °C

K = -40/+125 °C

Digital I/O lines	Number of ADC channels	Timed IO channels (PWM, capture)	External bus interface	CAN nodes	Ethernet	Communication interfaces	Additional features / remarks
33	10	23	✓	2	-	2x USIC	-
49	19	24	✓	2	-	2x USIC	CuWb
75	16	32	✓	3	-	6x USIC, 2x FlexRay	CuWb
118	24	32	✓	3	-	8x USIC, 2x FlexRay	CuWb
33	10	17	✓	-	-	1x USIC	-
33	10	17	✓	-	-	2x USIC	-
33	10	23	✓	2	-	2x USIC	-
49	19	24	✓	2	-	2x USIC	CuWb
38	9	20	✓	2	-	4x USIC	CuWb
76	16	24	✓	2	-	4x USIC	CuWb
76	16	37	✓	2	-	4x USIC	CuWb
119	24	44	✓	2	-	4x USIC	CuWb
119	24	60	✓	2	-	6x USIC	-
76	19	32	✓	2	-	10x USIC, 2x FlexRay	CuWb
118	28	44	✓	2	-	10x USIC, 2x FlexRay	CuWb

16-bit microcontroller

Product type	Automotive	Industrial	Consumer	Temperature ranges	Package	Max clock frequency [MHz]	Program memory [kByte]	SRAM (incl. cache) [kByte]	Co-processor
C166 family									
C161									
C161CS-LF	●	●	-	B, F, K	TQFP-128	25	256/-	10	-
C161O/K/S-LM/-L25M/3V	●	●	-	B, F	MQFP-80	20/25	-	2/1/2	-
C161PI-LM/-L25M/3V	●	●	-	B, F	MQFP-100	20/25	-	3	-
C161PI-LF/-L25F/3V	●	●	-	B, F	TQFP-100	20/25	-	3	-
C164									
C164CI/CL-8EM/-8E25M	●	●	-	F, K	MQFP-80	20/25	64	4	-
C164CI-LM/-L25M/3V	●	●	-	F, K	MQFP-80	20	-	4	-
C164CM-4EF	●	●	-	F, K	TQFP-64	20	32	2	-
C165									
C165-LF/-L25F/3V	●	●	-	B, F	TQFP-100	20/25	-	2	-
C165-LM/-L25M/3V	●	●	-	B, F	MQFP-100	20/25	-	2	-
C167									
C167SR-LM	●	●	-	F, B, K	MQFP-144	25	-	4	-
C167CS-L16M/-LM/-L33M/-L40M 3V	●	●	-	F, B, K	MQFP-144	16/25/33/40	-	11	-
XC166 family									
XC164CM									
XC164CM	●	●	-	F, K	TQFP-64	40	64-128	6-8	MAC
XC164CI									
XC161CI	●	●	-	F, K	TQFP-144	40	128	8	MAC
XC164CS									
XC164CS	●	●	-	F, K	TQFP-100	40	128-256	8-12	MAC
XC167CI									
XC167CI	●	●	-	F, K	TQFP-144	40	128-256	8-12	MAC

Digital I/O lines	Number of ADC channels	Timed I/O channels (PWM, capture)	External bus interface	CAN nodes	Ethernet	Communication interfaces	Additional features / remarks
93	12	32	✓	2	-	2x ASC, 1x SSC, 1x I ² C, J1850	ROM less
63	-	-	✓	-	-	1x ASC, 1x SSC	ROM less
76	4	-	✓	-	-	1x ASC, 1x SSC, 1x I ² C	ROM less
76	4	-	✓	-	-	1x ASC, 1x SSC, 1x I ² C	ROM less
59	8	12	✓	1	-	1x ASC, 1x SSC	OTP
59	8	12	✓	1	-	1x ASC, 1x SSC	ROM less
50	8	16	✓	1	-	1x ASC, 1x SSC	OTP
77	-	-	✓	-	-	1x ASC, 1x SSC	ROM less
77	-	-	✓	-	-	1x ASC, 1x SSC	ROM less
111	16	36	✓	-	-	1x UART, 1x SSC	ROM less
111	24	36	✓	2	-	1x UART, 1x SSC	ROM less
47	14	20	✓	2	-	2x ASC, 2x SSC	-
99	12	32	✓	2	-	2x ASC, 2x SSC, 1x SDLM, 1x I ² C, J1850	-
79	14	36	✓	2	-	2x ASC, 2x SSC	-
103	16	36	✓	2	-	2x ASC, 2x SSC, 1x I ² C	-

16-bit microcontroller

Product type	Automotive	Industrial	Consumer	Temperature ranges	Package	Max clock frequency [MHz]	Program memory [kByte]	SRAM (incl. cache) [kByte]	Co-processor
XE166 real time signal controller for industrial and multi market									
Classic series - alpha line									
XE164x	-	●	●	F, K	LQFP-100	66/80	768	24-82	MAC
XE167x	-	●	●	F, K	LQFP-144	66/80	768	28-82	MAC
U series - compact line									
XE161x	-	●	●	F, K	VQFN-48	40/66	64	8	MAC
L series - econo line									
XE161x	-	●	●	F, K	VQFN-48	66/80	128-160	12	MAC
XE162x	-	●	●	F, K	LQFP-64	66/80	96-160	12	MAC
N series - value line									
XE162xN	-	●	●	F, K	LQFP-64	80	128-320	18-34	MAC
XE164xN	-	●	●	F, K	LQFP-100	-	128-320	18-34	MAC
M series - base line									
XE162xM	-	●	●	F, K	LQFP-64	80	384-576	24-50	MAC
XE164xM	-	●	●	F, K	LQFP-100	80	384-576	26-50	MAC
XE167xM	-	●	●	F, K	LQFP-144	80	384-576	34-50	MAC
H series - high line									
XE167xH	-	●	●	F, K	LQFP-144	100	1.024-1.600	138	MAC
XE169xH	-	●	●	F, K	LQFP-176	100	1.024-1.600	138	MAC

ASC = Asynchronous Serial Channel

MAC = Multiply-Accumulate-Unit (DSP)

SDLM = Serial Data Link Module

SSC = Synchronous Serial Channel

USIC = ASC, SPI, I²C, I²S

B = 0/+70 °C

F = -40/+85 °C

K = -40/+125 °C

Digital I/O lines	Number of ADC channels	Timed I/O channels (PWM, capture)	External bus interface	CAN nodes	Ethernet	Communication interfaces	Additional features / remarks
75	11-16	30-37	✓	0-4	-	4-6x USIC	-
118	16-24	30-44	✓	0-5	-	4-6x USIC	-
33	10	15	-	-	-	2x USIC	-
33	10	21	-	1	-	4x USIC	-
48	19	21	-	2	-	4x USIC	CuWb
40	9	23	✓	0-2	-	6x USIC	CuWb
75	11-16	30	✓	0-2	-	4-6x USIC	CuWb
40	9	23	-	0-2	-	6x USIC	-
76	11-16	30-37	✓	0-4	-	4-6x USIC	CuWb
119	16-24	30-44	✓	0-6	-	4-8x USIC	CuWb
98-118	24	60	✓	6	-	10x USIC	-
98-118	30	60	✓	6	-	10x USIC	-

8-bit microcontroller

Product type	Automotive	Industrial	Consumer	Temperature ranges	Package	Max clock frequency [MHz]	Program memory [KByte]	SRAM (incl. cache) [KByte]	Co-processor
C500 family									
C505CA-4EM /-LM	•	•	•	F, B, K	MQFP-44	20	0	1.25	–
C515C-8EM	•	•	•	F, B, K	MQFP-80	10	64	2.25	–
XC800 family									
XC82x-series									
XC822MT	•	•	•	F, K	TSSOP-16	24	2–4	0.5	–
XC83x-series									
XC836MT	•	•	•	F, K, L	TSSOP-28	24	4–8	0.5	VC
XC86x-series									
XC866	•	•	•	F, K, A, L	TSSOP-38	26.67	4–16	0.75	–
XC866L	•	•	•	F, K, A, L	TSSOP-38	26.67	4–16	0.75	–
XC87x-series									
XC878	•	•	•	F, K, X	LQFP-64	27	52–64	3	[VC]
XC88x-series									
XC886	•	•	•	F, K, A, L	TQFP-48	24	24–32	1.75	[VC]
XC888	•	•	•	F, K, [A], [L]	TQFP-64	24	24–32	1.74	[VC]
CIC family (companion IC)									
CIC61508	•	•	–	K	TSSOP-38	26.67	–	0.25	–

[] = Optional features
HCP = High Current Pads
MAC = Multiply-Accumulate-Unit (DSP)
MDU = Multiply Divide Unit

LIN BSL = LIN Bootstrap Loader
SSC = Synchronous Serial Channel
TP = Touchpad Library in ROM
VC = Vector Computer (MDU + CORDIC)


A = -40/+140 °C
F = -40/+85 °C
K = -40/+125 °C
L = -40/+150 °C
X = -40/+105 °C

Digital I/O lines	Number of ADC channels	Timed I/O channels (PWM, capture)	External bus interface	CAN nodes	Ethernet	Communication interfaces	Additional features / remarks
34	8	4	-	1	-	1x USART	OTP, ROM less
49	8	4	-	1	-	1x USART, 1x SSC	OTP
17	4	4	-	-	-	1x UART, 1x SSC, LIN	-
25	8	4	-	-	-	1x UART, 1x SSC, LIN	-
27	8	4	-	-	-	1x UART, 1x SSC	-
27	8	4	-	-	-	1x UART, LIN BSL, 1x SSC	-
48	8	10	✓	[2]	-	2x UART, 1x SSC, [LIN]	-
34	8	4	-	[2]	-	2x UART, [LIN BSL], [1x SSC]	-
48	8	4	-	[2]	-	2x UART, [LIN BSL], [1x SSC]	-
-	-	-	-	-	-	Safety signature watchdog	Flash

Voltage regulators

Microcontroller family	Input voltage [V]	Input current (max) [mA]	Voltage regulator
XC8xx	5.0 ... 3.3	20	IFX20001/IFX24401/IFX2931/IFX25001/FX21401/IFX4949
XE166/XC2000	1.5 and 3.3 or 5.0	100	IFX25401/IFX24401/IFX2931/IFX4949
TriCore™	1.5 ... 3.3	> 400	IFX27001/IFX8117/IFX91041/IFX80471/IFX25001/IFX1117
XMC4000 series	3.3	300	IFX1763/IFX544xx
XMC1000 series	1.8 ... 5.5	< 100	IFX544xx/IFX542xx/IFX4949/IFX2931/IFX25001

Infineon microcontrollers roadmap





Where to buy

Infiniteon distribution partners and sales offices:

www.infineon.com/WhereToBuy

Service hotline

Infiniteon offers its toll-free 0800/4001 service hotline as one central number, available 24/7 in English, Mandarin and German.

- › Germany 0800 951 951 951 (German/English)
- › China, mainland 4001 200 951 (Mandarin/English)
- › India 000 800 4402 951 (English)
- › USA 1-866 951 9519 (English/German)
- › Other countries 00* 800 951 951 951 (English/German)
- › Direct access +49 89 234-0 (interconnection fee, German/English)

* Please note: Some countries may require you to dial a code other than "00" to access this international number.
Please visit www.infineon.com/service for your country!



Mobile product catalog

Mobile app for iOS and Android.

www.infineon.com

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2018 Infineon Technologies AG.
All rights reserved.

Order number: B158-10081-V5-7600-EU-EC-P
Date: 02/2018

Please note!

THIS DOCUMENT IS FOR INFORMATION PURPOSES ONLY AND ANY INFORMATION GIVEN HEREIN SHALL IN NO EVENT BE REGARDED AS A WARRANTY, GUARANTEE OR DESCRIPTION OF ANY FUNCTIONALITY, CONDITIONS AND/OR QUALITY OF OUR PRODUCTS OR ANY SUITABILITY FOR A PARTICULAR PURPOSE. WITH REGARD TO THE TECHNICAL SPECIFICATIONS OF OUR PRODUCTS, WE KINDLY ASK YOU TO REFER TO THE RELEVANT PRODUCT DATA SHEETS PROVIDED BY US. OUR CUSTOMERS AND THEIR TECHNICAL DEPARTMENTS ARE REQUIRED TO EVALUATE THE SUITABILITY OF OUR PRODUCTS FOR THE INTENDED APPLICATION.

WE RESERVE THE RIGHT TO CHANGE THIS DOCUMENT AND/OR THE INFORMATION GIVEN HEREIN AT ANY TIME.

Additional information

For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices, please contact your nearest Infineon Technologies office (www.infineon.com).

Warnings

Due to technical requirements, our products may contain dangerous substances. For information on the types in question, please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any life-endangering applications, including but not limited to medical, nuclear, military, life-critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury.