



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. BRASS PER QQ-B-613
- 3. NICKEL PL. 80 MIN. THICK OVER COPPER STRIKE
- 4. NICKEL PL. 80 MIN. THICK OVER COPPER PL 300 MIN. THICK
- 5. PHOSPHOR BRONZE PER QQ-B-750
- 6. GOLD FLASH OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 7. ZINC DIECAST

DIMENSIONS ARE IN MILLIMETERS	
UNLESS OTHERWISE SPECIFIED	TOLERANCES
0.5-6	= ±0.2
6-30	= ±0.4
30-120	= ±0.6
120-315	= ±1
315-1000	= ±1.6
1000-2000	= ±2.4

PART NO.	B6252HA-NPP3G-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'

Amphenol	
TITLE	BNC R/A PC MOUNT RECEPT. JACK
DRAWING NO.	KJ-B6252HA-NPP3G-50
ITEM NO.	

5	HEX NUT	NOTE 1	NOTE 3	1	HN14-1/2-28X25
4	LOCK WASHER	NOTE 2	NOTE 3	1	LW-158/13X05
3	CONTACT PIN	NOTE 5	NOTE 6	1	B6252HA-NPP3G
2	INSULATOR	P.P.	NATURAL		-50-G
1	BODY	NOTE 7	NOTE 4		

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	2.5/1	ISSUE	A	FILE NO.
-----	-------------	----------	--------	------	-------------	-------	-------	-------	---	----------

1. MAX. PANEL THICKNESS=5mm