






**.380 Spade
.031 Electro-Tinned Copper
16-14 AWG (Blue)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
6	X			B	✓	✓	4000	50391	
		X		B	✓	✓	3000	50391-8	
			X	B	✓	*	3000	50391-8A	
	X			W	✓	✓	4000	50392	
		X		W	✓	✓	3000	50392-8	
			X	W	✓	*	3000	50392-8A	
8	X			B	✓	✓	4000	50403	
		X		B	✓	✓	3000	50403-8	
			X	B	✓	*	3000	50403-8A	
	X			W	✓	✓	4000	50404	
		X		W	✓	✓	3000	50404-8	
			X	W	✓	*	3000	50404-8A	
10	X			B	✓	✓	4000	50415	
		X		B	✓	✓	3000	50415-8	
			X	B	✓	*	3000	50415-8A	
	X			W	✓	✓	4000	50416	
		X		W	✓	✓	3000	50416-8	
			X	W	✓	*	3000	50416-8A	

**.500 Spade
.031 Electro-Tinned Copper
16-14 AWG (Blue)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
10	X			B	✓	✓	4000	50613	
		X		B	✓	✓	3000	50613-8	
			X	B	✓	*	3000	50613-8A	
	X			W	✓	✓	4000	50614	
		X		W	✓	✓	3000	50614-8	
			X	W	✓	*	3000	50614-8A	
1/4	X			B	✓	✓	4000	50625	
		X		B	✓	✓	3000	50625-8	
			X	B	✓	*	3000	50625-8A	
	X			W	✓	✓	4000	50626	
		X		W	✓	✓	3000	50626-8	
			X	W	✓	*	3000	50626-8A	

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.