

LED display

单桁LED数字表示

1 Digit LED numeric display

Ta=25°C

Character height 字高	機種名 Type No.		ピーク発光波長 Peak-emission wavelength	絶対最大定格 Absolute maximum ratings					推奨動作電流 Recommend. If/seg	電気的光学的特性 Electro-optical characteristics				
	Com.-Anode	Com.-Cathode		nm (Color)	If/seg	IP/seg	Vr/seg	Pd		Topt	Vf Typ.	If	Luminous intensity Lv Typ.	If
mm				mA	mA	V	W	°C	mA	V	mA	μcd/seg	mA	(V _R =8V) μA/seg
14.3	★SL-5125	★SL-5126	630 (U.R)	20	40	3	0.65	-25~+70	10~15	2.0	15	2700	15	10
			567 (Y.G)											
	SL-1199	SL-1190	700 (R)	20	40	3	0.35	-25~+70	3~10	1.9	5	300	5	10
	SL-2199	SL-2190	565 (G)	20	40	3	0.4	-25~+70	10~15	2.05	15	2000	15	10
	SL-1129	SL-1120	700 (R)	20	40	3	0.75	-25~+70	3~10	1.9	5	300	5	10
	SL-2129	SL-2120	565 (G)	20	40	3	0.8	-25~+70	10~15	2.05	15	1100	15	10
25.4	SL-8139	SL-8130	660 (U.H.R)	20	40	3	0.58	-25~+70	10~15	3.5	20	20000	20	10
	SL-5139	SL-5130	630 (U.R)	20	40	3	1.4	-25~+70	10~15	4.0	15	5000	15	10
			567 (Y.G)											
	SL-5139-10	SL-5130-10	660 (U.H.R)	20	40	3	1.3	-25~+70	10~15	3.5	20	20000	20	10
567 (Y.G)														

★開発中 ★Under development.

外観図 Package dimensions

Tolerance : ±0.25
Unit : mm

