



\*) only for contact L=9 mm

UNIT:mm

Z= 0	--->	L=6.0 mm
Z= 1	--->	L=8.0 mm
Z= 2	--->	L=9.0 mm
Z= 3	--->	L=10.0mm
Z= 4	--->	L=12.0mm
Z= 5	--->	L=13.0mm
Z= 6	--->	L=15.0mm
Z= 7	--->	L=18.0mm
Z= 8	--->	L=22.0mm
Z= 9	--->	L=33.0mm

INDEX		DATE	
XX=N= Number of contacts (04+72) Standard number of contacts (xx): 40; 44; 56; 64; 72 Z = pin lenght (see table)			
MODIFICATION		Material: Shell: Thermoplastic Polyester UL94V0 Sleeve and pin contact: screw machined brass; clip: beryllium-copper	
Platings: _____		Sleeve: 5µm Sn ; Clip: 0.75µm Au	
Notes: _____		Accept pins ø040-0.56mm	
Denomination: PCB FEMALE		Cod. 87795291XX49Z	
Turned connector, double row, pitch 2.54		File: 87795291XX4YZ	
Dis. Nr. _____		Contr. Ponderazio M	
index		Date 22-04-04	
_____		Design Chiappini, R	
_____		_____	

