

DIL 14 PACKAGE TCXO

DFA 14-K (5 V) & DFA 14-L (3.3 V)

KEY FEATURES

2 to 52 MHz

Tight stability



Analogue temperature compensation

APPLICATIONS

SDH/Sonet/Microwave

Function	DFA 14
NC/Pot in/Vco	1
GND	7
Output	8
Vcc	14

H = 8.50 mm



Option Y

TYPE	DFA 14-KH	DFA 14-KO	DFA 14-LH	DFA 14-LO
Frequency Range	2 to 52 MHz	2 to 52 MHz	2 to 45 MHz	2 to 45 MHz

ELECTRICAL SPECIFICATIONS					
supply voltage		5 V ± 5 %	5 V ± 5 %	3.2 V to 3.6 V	3.2 V to 3.6 V
supply current (no loa)d	≤ 25 MHz	≤ 10 mA	≤ 5 mA	≤ 5 mA	≤ 5 mA
	≤ 35 MHz	≤ 20 mA	≤ 20 mA	≤ 15 mA	≤ 15 mA
	> 35 MHz	≤ 30 mA	≤ 30 mA	≤ 20 mA	≤ 20 mA
output load		HCMOS 15 pF or 2 TTL	clipped sine 20kΩ/5 pF	HCMOS 15 pF or 1 TTL	clipped sine 20kΩ/5 pF
duty cycle @ 2.5V (LH @ 1.65 V)		≤ 45/55...55/45 %		≤ 45/55...55/45 %	
rise/fall times (10 to 90 %)		≤ 10 ns		≤ 10 ns	
high/low levels or output amplitude		≥ 3.5 V/ ≤ 0.5 V	≥ 2 V p-p	≥ 2.7 V/ ≤ 0.2 V	≥ 1.5 V p-p
start-up		≤ 10 ms @ 4.75 V	≤ 10 ms @ 4.75 V	≤ 10 ms @ 3.2 V	≤ 10 ms @ 3.2 V
remarks	duty cycle for frequencies > 30 MHz is 40/60%...60/40%				

FREQUENCY STABILITY			detailed tolerances [ppm]			
type	temperature range	model code	temperature	stability versus:		
				Vcc range	load ± 10 %	ageing
all types	-10 to 60°C	D1	≤ ± 1	≤ ± 0.1	≤ ± 0.1	≤ ± 1
	-20 to 70°C	C1	≤ ± 1			
		C2	≤ ± 2			
	-30 to 75°C	N2	≤ ± 2			
DFA 14-K types	-40 to 85°C	E5	≤ ± 5	≤ ± 0.1	≤ ± 0.1	≤ ± 1
		E3	≤ ± 3			
		E2	≤ ± 2			
remarks			factory calibration if no trimming option ≤ ± 1 ppm			
			ageing is 1 st year at 25°C			
			DFA S7-L : Vcc range ≤ ± 0.3 ppm (f ≥ 30 MHz)			

OPTIONS	CODE	
external voltage control	V	DFA 14-K : 2.5 V ± 2 V ≥ ± 5 ppm, positive slope DFA 14-L : 1.5 V ± 1.5 V ≥ ± 5 ppm, positive slope
internal trimmer	A	≥ ± 5 ppm
external potentiometer	Y	10 kΩ ≥ ± 5 ppm (not available with internal trimmer)

ORDERING CODE	type + option code + frequency + model code
Example	DFA 14-KHAV 8.192 MHz E2