

PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

200V N-Channel Enhancement Mode MOSFET


Voltage	200 V	Current	18 A
----------------	--------------	----------------	-------------

Features

- $R_{DS(ON)}$, $V_{GS}@10V, I_D@9A < 160m\Omega$
- High switching speed
- Improved dv/dt capability
- Low Gate Charge
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : TO-251AA, TO-252AA, TO-220AB, ITO-220AB-F Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- TO-251AA Approx. Weight : 0.0104 ounces, 0.297grams
- TO-252AA Approx. Weight : 0.0105 ounces, 0.297grams
- TO-220AB Approx. Weight : 0.067 ounces, 1.89 grams
- ITO-220AB-F Approx. Weight : 0.068 ounces, 2 grams



Maximum Ratings and Thermal Characteristics ($T_A=25^{\circ}C$ unless otherwise noted)

PARAMETER		SYMBOL	TO-251AA TO-252AA	TO-220AB	ITO-220AB-F	UNITS
Drain-Source Voltage		V _{DS}	200			V
Gate-Source Voltage		V _{GS}	±20			
Continuous Drain Current	T _C =25°C	I _D	18			A
	T _C =100°C		11			
Pulsed Drain Current ^(Note 1)		I _{DM}	72			
Power Dissipation	T _C =25°C	P _D	83	89	50	W
	T _C =100°C		33	35.6	20	
Single Pulse Avalanche Energy ^(Note 6)		E _{AS}	72			mJ
Operating Junction and Storage Temperature Range		T _J ,T _{STG}	-55~150			°C
Typical Thermal Resistance ^(Note 4,5)						
- Junction to Case		R _{θJC}	1.5	1.4	2.5	°C/W
- Junction to Ambient		R _{θJA}	110	62.5	120	

- Limited only By Maximum Junction Temperature



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V,I _D =250uA	200	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} ,I _D =250uA	1	1.83	3	
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =10V,I _D =9A	-	126	160	mΩ
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =200V,V _{GS} =0V	-	-	1.0	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =+20V,V _{DS} =0V	-	-	+100	nA
Dynamic (Note 7)						
Total Gate Charge	Q _g	V _{DS} =160V, I _D =18A, V _{GS} =10V (Note 2,3)	-	24	-	nC
Gate-Source Charge	Q _{gs}		-	3.7	-	
Gate-Drain Charge	Q _{gd}		-	6.1	-	
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V, f=1.0MHZ	-	1017	-	pF
Output Capacitance	C _{oss}		-	148	-	
Reverse Transfer Capacitance	C _{rss}		-	36	-	
Turn-On Delay Time	td(on)	V _{DD} =100V, I _D =18A, V _{GS} =10VR _G =25Ω (Note 2,3)	-	15	-	ns
Turn-On Rise Time	t _r		-	61	-	
Turn-Off Delay Time	td(off)		-	104	-	
Turn-Off Fall Time	t _f		-	99	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I _S	---	-	-	18	A
Maximum Pulsed Drain-Source Diode Forward Current	I _{SM}	---	-	-	72	
Diode Forward Voltage	V _{SD}	I _S =1A,V _{GS} =0V	-	0.73	1.0	V

NOTES :

- Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$
- Essentially independent of operating temperature typical characteristics.
- Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}=150^{\circ}\text{C}$. Ratings are based on low frequency and duty cycles to keep initial $T_J=25^{\circ}\text{C}$.
- The maximum current rating is package limited.
- $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch² with 2oz.square pad of copper.
- The test condition is $L=1\text{mH}$, $I_{AS}=12A$, $V_{DD}=50V$, $R_G=25\text{ohm}$, Starting $T_J=25^{\circ}\text{C}$
- Guaranteed by design, not subject to production testing.

PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with V_{GS}










Fig.6 Source-Drain Diode Forward Voltage

PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

TYPICAL CHARACTERISTIC CURVES



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

TYPICAL CHARACTERISTIC CURVES




Fig.13 PJF18N20 Maximum Safe Operating Area




Fig.14 PJU/D Normalized Transient Thermal Impedance




Fig.15 PJP Normalized Transient Thermal Impedance






Fig.16 PJF Normalized Transient Thermal Impedance

Packaging Information


Unit: inch(mm)




Unit: inch(mm)



Unit: inch(mm)



Unit: inch(mm)




PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
PJU18N20_TO_00001	TO-251AA	80pcs / Tube	U18N20	Halogen free
PJD18N20_L2_00001	TO-252AA	3,000pcs / 13" reel	D18N20	Halogen free
PJP18N20_TO_00001	TO-220AB	50pcs / Tube	P18N20	Halogen free
PJF18N20_TO_00001	ITO-220AB-F	50pcs / Tube	F18N20	Halogen free

Mounting Pad Layout





PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panjit:

[PJP18N20_T0_00001](#)