

DELPHI Connection Systems Catalog

Customer Service

Comparison List (0)

Samples Request

Find by Feature

Browse by Category

Browse by Application

Share

Search

Enter part number or keyword

Search Results (1)

Search

Options

1 Result(s): [All] - 12146940

Compare

12146940 - Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2

Compare

Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2

Part # 12146940





Question about this product?



Attributes


Documents (2)

Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	✓ 12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Part # :	12146940
Description :	Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2
Description :	Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2
Description :	Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2
Description :	✓ Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2
Description :	Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2
Description :	Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2
Description :	Metri-Pack 800 Series Male Unsealed Silver Plating Terminal, Cable Range 6.00 - 8.00 mm2

Sealable :	Unsealed
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	✓ CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Material :	CU ALLOY
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	✓ 3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Weight [g] :	3
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	✓ Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver

Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Plating :	Silver
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	 4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Minimum Cable Diameter [mm] :	4.50
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	 5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Maximum Cable Diameter [mm] :	5.55
Minimum Cable Core Cross Section [mm ²] :	6.00
Minimum Cable Core Cross Section [mm ²] :	6.00
Minimum Cable Core Cross Section [mm ²] :	6.00

Minimum Cable Core Cross Section [mm2] :	 6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Minimum Cable Core Cross Section [mm2] :	6.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	 8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00
Maximum Cable Core Cross Section [mm2] :	8.00



[Suppliers](#) | [Terms of Use](#) | [Privacy](#) | [Mexico Privacy Statement](#) | [Cookie Policy](#) | [Sitemap](#) | [European Safe Harbor](#) | [California Supply Chains Act](#)

© Delphi Automotive LLP. All rights reserved.