




SPECIFICATIONS

- 1.Body : Brass,QQ-B-626
Gold Plated 3 Micro-Inches Min Thick Over Nickel
Plated 70Micro-Inches Min. Over Copper Strike
- 2.Insulator:Teflon MIL-P-19468,White
- 3.Contact Pin : Brass,QQ-B-626
Gold Plated 30 Micro-Inches Min Over Nickel
Plated 70Micro-Inches Min. Thick Over Copper Strike
- 4.Washer : Brass,QQ-B-613
Gold Plated 3 Micro-Inches Min Over Nickel
Plated 70Micro-Inches Min. Over Copper Strike
- 5.Nut : Brass,QQ-B-613
Gold Plated 30 Micro-Inches Min Over Nickel
Plated 70Micro-Inches Min. Thick Over Copper Strike



Recommended Mounting Hole

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY MEI		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X .XX ±0.20 AWG. ±5°					
PART No. SMB-JSB50R		CHECKED BY BECKY							
DRAWING No. SMB-JSB50R		DRAWING BY HZF							
SCALE	NONE	REV.	A		UNIT mm		AREA	REVISIONS	CHK